



 PRODUCT-DETAILS

S802S-D50

S802S-D50 High Performance MCB



General Information

| | |
|-----------------------|--------------------------------|
| Extended Product Type | S802S-D50 |
| Product ID | 2CCS862001R0501 |
| EAN | 7612271201159 |
| Catalog Description | S802S-D50 High Performance MCB |

| | |
|------------------|--|
| Long Description | <p>The S802S-D50 is a 2-pole High Performance Circuit breaker with D-Characteristic, with cage terminal and a rated current of 50 A. It is a current limiting device with a maximum breaking capacity of 50kA at 240/415V. It can be used for voltages up to 400/690V and in DC as well. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S802S-D50 complies with IEC/EN 60898-1 and IEC/EN 60947-2 and allows the use for residential, commercial and industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S802S-D50 more comfortable. Due to the fast arc extinction of S802S-D50 your application will be secured.</p> |
|------------------|--|

ABB EcoSolutions

| | |
|---------------------------|--|
| ABB EcoSolutions | Yes |
| EcoSolutions Profile | 9AKK108471A1082 |
| Recyclability Rate of the | Design for Closing Resource Loops - Standard EN45555 - 86.29 % |

| | |
|--|--|
| Product acc. to EN45555 | |
| ABB Site Meeting Group Waste To Landfill Target | No non-hazardous waste is sent to a landfill |
| End Of Life Disassembling Instructions | 9AKK108470A2575 |
| Environmental Product Declaration - EPD | 9AKK108470A1695,9AKK108470A1696 |

Technical

| | |
|---|--|
| Type of Residual Current | Standard Version |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) | (415 V AC) 50 kA (440 V AC) 30 kA (500 V AC) 15 kA (690 V AC) 6 kA (250 V DC) 30 kA |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}) | (415 V AC) 40 kA (440 V AC) 22.5 kA (500 V AC) 11 kA (690 V AC) 4 kA (250 V DC) 30 kA |
| Contact Position Indication | ON / OFF / TRIP |
| Energy Limiting Class | 3 |
| Electrical Endurance | 6000 cycle |
| Mechanical Endurance | 6000 cycle |
| Number of Protected Poles | 2 |
| Number of Poles | 2P |
| Tightening Torque | 3.5 N·m 31 in·lb |
| Release Type | D |
| Actuator Marking | I / O |
| Recommended Screw Driver | Pozidriv 2 |
| Accessories Available | Yes |
| Remarks | Connection from top and bottom Connecting with CU only IP40 in enclosure with cover Cage terminal with captive screw |
| Connecting Capacity | Flexible 0 ... 50 mm ² Rigid 0 ... 70 mm ² |
| Terminal Type | Screw Terminals |

Electrical

| | |
|--|--|
| Tripping Characteristic | D |
| Rated Operational Voltage | acc. to IEC 60898-1 400 V AC acc. to IEC 60947-2 690 V AC |
| Operational Voltage | Maximum 230/400 V AC Minimum 12 V AC |
| Rated Insulation Voltage (U_i) | acc. to IEC/EN 60664-1 690 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 8 kV |
| Input Voltage Type | AC/DC |
| Rated Current (I_n) | 50 A |
| Rated Short-Circuit Capacity | (400 V AC) 25 kA |

| | |
|----------------------|--|
| Frequency (f) | 50 ... 60 Hz |
| Rated Frequency (f) | 50/60 Hz |
| Power Loss | Total 12.8 W at Rated Operating Conditions per Pole 6.4 W |
| Overvoltage Category | IV |

Design

| | |
|------------------|------------------------------|
| Housing Material | Insulation group I, RAL 7035 |
|------------------|------------------------------|

Technical UL/CSA

| | |
|------------------------------------|---|
| Interrupting Rating acc. to UL1077 | (480Y / 277 V AC) 14 kA (600Y / 347 V AC) 6 kA |
|------------------------------------|---|

Material Compliance

| | |
|---|--|
| RoHS Declaration | 2CCC005083D0202 |
| RoHS Information | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 20211214 |
| REACH Declaration | 9AKK108470A9089 |
| REACH Information | False - does not contain substances > 0.1 mass percentage |
| REACH Date | 20250313 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |

Environmental

| | |
|-----------------------------------|--|
| Ambient Air Temperature | Operation -40 ... 70 °C Storage -40 ... 70 °C |
| Reference Ambient Air Temperature | acc. to IEC60947-2 30 °C acc. to EN60898-1 30 °C |
| Degree of Protection | IP20 |
| Pollution Degree | 3 |
| Resistance to Vibrations | 1 mm 2 - 13.2 Hz 0.7g with Load 100% x le 13.2 - 100 Hz |
| Environmental Information | 2CCY413207D0203 |

Dimensions

| | |
|-------------------------------------|-----------------|
| Width in Number of Modular Spacings | 3 |
| Product Net Width | 54 mm |
| Product Net Height | 95 mm |
| Product Net Depth / Length | 82.5 mm |
| Product Net Weight | 490 g |
| Built-In Depth (t ₂) | 82.5 mm |
| Dimension Diagram | 2CCC413003C0201 |

Engineering

EPLAN Data

9AAC172534_EPLAN

Ordering

| | |
|------------------------------|-------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Gross Weight | 510 g |
| E-Number (Finland) | 3212232 |
| E-Number (Norway) | 1628815 |
| E-Number (Switzerland) | 807754315 |

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| CB Certificate | 9AKK107680A0857 |
| CCC Certificate | 9AKK108469A3021 |
| Declaration of Conformity - CE | 2CCC005083D0202 |
| DNV GL Certificate | 2CCC413018D0201 |
| ESTI Certificate | 2CCC413020D0101 |
| KC Certificate | 9AKK107680A0932 |
| LR Certificate | 2CCC413017D0201 |
| RINA Certificate | 2CCC413019D0201 |
| UL Certificate | 9AKK107680A2286 |
| VDE Certificate | 2CCC413039D0601 |

Installation

| | |
|--------------------------|--|
| Instructions and Manuals | 2CCC413016M0008 |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting Position | Any |

Popular Downloads

| | |
|-----------------------------------|---|
| Data Sheet, Technical Information | 9AKK108468A9560 9AKK108468A9561 9AKK108468A9562 |
|-----------------------------------|---|

External Classifications and Standards

| | |
|------------------------------------|--|
| ETIM 9 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 10 | EC000042 - Miniature circuit breaker (MCB) |
| UNSPSC | 39121603 |
| eClass | V11.0 : 27141901 |
| IDEA Granular Category Code (IGCC) | 4899 >> Miniature circuit breaker (MCB) screw-in model |
| Object Classification Code | F |
| Standards | IEC/EN 60947-2 |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs → High Performance Circuit Breakers HPCBs - S800

