



PRODUCT-DETAILS

S801U-K60

S801U-K60 High Performance MCB



General Information	
Extended Product Type	S801U-K60
Product ID	2CCS881017R0587
EAN	7612271214289
Catalog Description	S801U-K60 High Performance MCB
Long Description	S801U-K60 1 Pole K Characteristic 60A 30kA 240/415VAC High Performance Circuit Breaker HPCB

ABB EcoSolutions	
ABB EcoSolutions	Yes
EcoSolutions Profile	9AKK108471A1082
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 86.29 %
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill
End Of Life Disassembling Instructions	9AKK108470A2575
Environmental Product	9AKK108470A1695,9AKK108470A1696

Declaration - EPD

Technical

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 V AC) 30 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 25 kA
Contact Position Indication	ON / OFF / TRIP
Energy Limiting Class	3
Number of Protected Poles	1
Number of Poles	1P
Release Type	K
Actuator Marking	I / O
Accessories Available	Yes
Connecting Capacity	Flexible 0 ... 50 mm ² Rigid 0 ... 70 mm ²

Electrical

Short-Circuit Current Rating (SCCR)	(240 V AC) 30 kA
Tripping Characteristic	K
Rated Operational Voltage	acc. to IEC 60947-2 240 V AC UL489 240 V AC
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 690 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Input Voltage Type	AC
Rated Current (I_n)	60 A
Frequency (f)	50/60 Hz
Rated Frequency (f)	50/60 Hz
Power Loss	Total 5.8 W at Rated Operating Conditions per Pole 5.8 W
Overvoltage Category	III

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 30 kA
-----------------------------------	------------------

Material Compliance

RoHS Declaration	2CCC005116D0201
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20250625
REACH Declaration	9AKK108470A9089
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20250313

Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +70 °C
Degree of Protection	IP20
Pollution Degree	2
Environmental Information	2CCY413207D0203

Dimensions

Width in Number of Modular Spacings	1.5
Product Net Width	27 mm
Product Net Height	95 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	245 g
Built-In Depth (t ₂)	82.5 mm
Dimension Diagram	2CCC413003C0201

Engineering

EPLAN Data	9AAF622564_EPLAN
------------	------------------

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	270 g

Certificates and Declarations

Declaration of Conformity - CE	2CCC413009D0201
UL Certificate	9AKK107680A2289

Installation

Instructions and Manuals	2CCC413015M0403
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK108468A9560 9AKK108468A9561
-----------------------------------	------------------------------------

9AKK108468A9562

External Classifications and Standards

ETIM 9	EC000042 - Miniature circuit breaker (MCB)
ETIM 10	EC000042 - Miniature circuit breaker (MCB)
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4899 >> Miniature circuit breaker (MCB) screw-in model
Object Classification Code	F
Standards	UL 489

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs → High Performance Circuit Breakers HPCBs - S800

