



PRODUCT-DETAILS

# ST201M-Z13

## Miniature Circuit Breaker - ST200M - 1P - 13 A - Z



### General Information

Extended Product Type	ST201M-Z13
Product ID	2CDS271334R0448
EAN	4016779018104
Catalog Description	Miniature Circuit Breaker - ST200M - 1P - 13 A - Z
Long Description	ST201M-Z13 Miniature Circuit Breaker ST201M-Z13 Miniature Circuit Breaker Z-Char., 10kA, 13A, 1P

### ABB EcoSolutions

ABB EcoSolutions	Yes
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 80.7 %
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill
Extended Product Lifetime	Product Durability
End Of Life Disassembling Instructions	9AKK108468A3132

Environmental Product  
Declaration - EPD

9AKK108467A7832

## Technical

Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(230 V AC) 15 kA (230 V) 15 kA
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(230 V AC) 11.2 kA
Energy Limiting Class	3
Number of Protected Poles	1
Number of Poles	1P
Accessories Available	Yes
Connecting Capacity	Flexible 25 ... 25 mm <sup>2</sup> Rigid 35 ... 35 mm <sup>2</sup>
Terminal Type	Double Clamp

## Electrical

Tripping Characteristic	Z
Rated Operational Voltage	acc. to IEC 60947-2 230 V
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage ( $U_{imp}$ )	4 kV
Input Voltage Type	AC/DC
Rated Current ( $I_n$ )	13 A
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(230 V) 15 kA (400 V) 15 kA
Rated Frequency (f)	50 / 60 Hz
Power Loss	1.4 W
Overvoltage Category	III

## Technical UL/CSA

Interrupting Rating acc. to UL1077	(277 V AC) 10 kA (60 V DC) 10 kA
------------------------------------	-------------------------------------

## Material Compliance

RoHS Declaration	9AKK108472A0372
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20251203
REACH Declaration	9AKK107492A1906
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20251029
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Toxic Substances	9AKK108468A8104

Control Act - TSCA

WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B Business To Business

---

## Environmental

Ambient Air Temperature Operation -25 ... +55 °C

Degree of Protection IP20

Pollution Degree 3

---

## Dimensions

Width in Number of Modular Spacings 1.0

Product Net Width 17.5 mm

Product Net Height 88 mm

Product Net Depth / Length 69 mm

Product Net Weight 0.115 kg

Built-In Depth (t<sub>2</sub>) 69 mm

---

## Ordering

Package Level 1 Units carton 10 piece

Package Level 1 Gross Weight 1.19 kg

---

## Certificates and Declarations

Declaration of Conformity - CE 2CDK400679D2703

Declaration of Conformity - UKCA 9AKK108467A5200

---

## Installation

Instructions and Manuals 9AKK107046A3150

---

## Popular Downloads

Data Sheet, Technical Information 9AKK107046A3150

---

## External Classifications and Standards

ETIM 9 EC000042 - Miniature circuit breaker (MCB)

ETIM 10 EC000042 - Miniature circuit breaker (MCB)

UNSPSC 39121603

eClass V11.0 : 27141901

IDEA Granular Category 4899 &gt;&gt; Miniature circuit breaker (MCB) screw-in model

Code (IGCC)

Standards

CSA 22.2 No. 235  
IEC/EN 60947-2  
UL 1077

Certification Agency

CSA  
EN  
IEC  
UL

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs → ST200M



360°

