




---

 PRODUCT-DETAILS

## ST201M-K4NA

### Miniature Circuit Breaker - ST200M - 1P+N - 4 A - K




---

**General Information**

|                       |  |
|-----------------------|--|
| Extended Product Type | ST201M-K4NA  |
| Product ID            | 2CDS271335R0337  |
| EAN                   | 4016779019965  |
| Catalog Description   | Miniature Circuit Breaker - ST200M - 1P+N - 4 A - K  |
| Long Description      | ST201M-K4NA Miniature Circuit Breaker ST201M-K4NA Miniature Circuit Breaker K-Char., 10kA, 4A, 1P+NA |

---

**ABB EcoSolutions**

|   |   |
|---|---|
| ABB EcoSolutions                                  | Yes   |
| Recyclability Rate of the Product acc. to EN45555 | Design for Closing Resource Loops - Standard EN45555 - 80.7 % |
| ABB Site Meeting Group Waste To Landfill Target   | No non-hazardous waste is sent to a landfill                  |
| Extended Product Lifetime                         | Product Durability  |
| End Of Life Disassembling Instructions            | 9AKK108468A3132   |

Environmental Product  
Declaration - EPD

9AKK108467A7832

## Technical

|   |   |
|---|---|
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (230 V AC) 15 kA<br>(230 V) 15 kA                                     |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (230 V AC) 11.2 kA  |
| Energy Limiting Class                                       | 3   |
| Number of Protected Poles                                   | 1   |
| Number of Poles   | 1P+N  |
| Accessories Available                                       | Yes   |
| Connecting Capacity   | Flexible 25 ... 25 mm <sup>2</sup><br>Rigid 35 ... 35 mm <sup>2</sup> |
| Terminal Type   | Double Clamp  |

## Electrical

|  |                                |
|--|--------------------------------|
| Tripping Characteristic                              | K                              |
| Rated Operational Voltage                            | acc. to IEC 60947-2 230 V AC   |
| Rated Insulation Voltage ( $U_i$ )                   | acc. to IEC/EN 60664-1 440 V   |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )        | 4 kV                           |
| Input Voltage Type                                   | AC/DC                          |
| Rated Current ( $I_n$ )                              | 4 A                            |
| Rated Conditional Short-Circuit Current ( $I_{nc}$ ) | (230 V) 15 kA<br>(400 V) 15 kA |
| Rated Frequency (f)                                  | 50 / 60 Hz                     |
| Overvoltage Category                                 | III                            |

## Technical UL/CSA

|                                    |                  |
|------------------------------------|------------------|
| Interrupting Rating acc. to UL1077 | (277 V AC) 10 kA |
|------------------------------------|------------------|

## Material Compliance

|   |  |
|---|--|
| RoHS Declaration                            | 9AKK108472A0372  |
| RoHS Information                            | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date                                   | 20251203   |
| REACH Declaration                           | 9AKK107492A1906  |
| REACH Information                           | False - does not contain substances > 0.1 mass percentage              |
| REACH Date                                  | 20251029   |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363  |
| Toxic Substances Control Act - TSCA         | 9AKK108468A8104  |

|                |  |
|----------------|--|
| SCIP           | 171856b6-03a8-4c04-9bae-ec01c5a7d7da Germany               |
| WEEE Category  | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business                                       |

**Environmental**

|                         |                          |
|-------------------------|--------------------------|
| Ambient Air Temperature | Operation -25 ... +55 °C |
| Degree of Protection    | IP20                     |
| Pollution Degree        | 3                        |

**Dimensions**

|                                     |          |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 2        |
| Product Net Width                   | 35 mm    |
| Product Net Height                  | 88 mm    |
| Product Net Depth / Length          | 69 mm    |
| Product Net Weight                  | 0.217 kg |
| Built-In Depth (t <sub>2</sub> )    | 69 mm    |

**Ordering**

|                              |                |
|------------------------------|----------------|
| Package Level 1 Units        | carton 5 piece |
| Package Level 1 Gross Weight | 1.125 kg       |
| Replacement Product ID (NEW) | No replacement |

**Certificates and Declarations**

|                                  |                 |
|----------------------------------|-----------------|
| Declaration of Conformity - CE   | 2CDK400679D2703 |
| Declaration of Conformity - UKCA | 9AKK108467A5200 |

**Installation**

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 9AKK107046A3150 |
|--------------------------|-----------------|

**Popular Downloads**

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107046A3150 |
|-----------------------------------|-----------------|

**External Classifications and Standards**

|         |  |
|---------|--|
| ETIM 9  | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 10 | EC000042 - Miniature circuit breaker (MCB) |
| UNSPSC  | 39121603                                   |

|                                    |  |
|------------------------------------|--|
| eClass                             | V11.0 : 27141901                                       |
| IDEA Granular Category Code (IGCC) | 4899 >> Miniature circuit breaker (MCB) screw-in model |
| Standards                          | CSA 22.2 No. 235<br>IEC/EN 60947-2<br>UL 1077          |
| Certification Agency               | CSA<br>EN<br>IEC<br>UL                                 |

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs → ST200M



360°

