



PRODUCT-DETAILS

# SU203M-C0.5

Miniature Circuit Breaker - SU200M - 3P - 0.5 A  
- C - (400 V AC) 11.2 kA



General Information	
Extended Product Type	SU203M-C0.5
Product ID	2CDS273337R0984
EAN	4016779931205
Catalog Description	Miniature Circuit Breaker - SU200M - 3P - 0.5 A - C - (400 V AC) 11.2 kA
Long Description	SU203M-C0,5 Miniature Circuit Breaker C-Char., UL10kA, IEC15kA, 0,5A, 3P UL489

ABB EcoSolutions	
ABB EcoSolutions	Yes
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 62 %
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill
Extended Product Lifetime	Product Durability
End Of Life Disassembling Instructions	9AKK108471A4773
Environmental Product	9AKK108470A9950

## Declaration - EPD

**Technical**

Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(400 V AC) 15 kA (400 V) 15 kA
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(400 V AC) 11.2 kA
Power Supply Connection	Arbitrary
Contact Position Indication	Red ON / Green OFF
Energy Limiting Class	3
Mechanical Endurance	20000 cycle
Number of Protected Poles	3
Number of Poles	3P
Tightening Torque	2.8 N·m
Actuator Type	Toggle
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Actuator Marking	I / O
Actuator Material	Insulation Group II, Black, Sealable
Recommended Screw Driver	Pozidriv 2
Accessories Available	Yes
Connecting Capacity	Busbar 10/10 mm <sup>2</sup> Flexible with Ferrule 0.75 ... 25 mm <sup>2</sup> Flexible 0.75 ... 25 mm <sup>2</sup> Flexible 0.75 ... 25 mm <sup>2</sup> Rigid 0.75 ... 35 mm <sup>2</sup> Stranded 0.75 ... 35 mm <sup>2</sup>
Installation Size	acc. to DIN 43880 3
Terminal Type	Double Clamp

**Electrical**

Tripping Characteristic	C
Rated Operational Voltage	acc. to IEC 60898-1 400 V AC acc. to IEC 60947-2 400 V AC
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage ( $U_{imp}$ )	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Input Voltage Type	AC/DC
Rated Current ( $I_n$ )	0.5 A
Rated Short-Circuit Capacity	(400 V AC) 11.2 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(400 V) 15 kA
Rated Frequency (f)	50 / 60 Hz DC
Power Loss	4.2 W at Rated Operating Conditions per Pole 1.4 W
Overvoltage Category	III

## Design

Housing Material	Insulation Group I, RAL 7035
------------------	------------------------------

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	480Y / 277 V AC
Interrupting Rating acc. to UL489	(240 V AC) 10 kA (480Y / 277 V AC) 10 kA
Connecting Capacity UL/CSA	Busbar 18-8 AWG Conductor 18-4 AWG

## Material Compliance

RoHS Declaration	9AKK108472A0372
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20251203
REACH Declaration	9AKK107492A1906
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20251029
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Toxic Substances Control Act - TSCA	9AKK108468A8104
SCIP	89318623-ff2d-4ce0-ae0e-5d16fac11138 Germany
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

## Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
Degree of Protection	IP20 IP40 Enclosure with Cover IP40
Pollution Degree	3
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
Environmental Information	9AKK107680A9140

## Dimensions

Width in Number of Modular Spacings	3
Product Net Width	52.5 mm
Product Net Height	111 mm
Product Net Depth / Length	69 mm

Product Net Weight	0.366 kg
Pole Net Weight	0.125 kg
Built-In Depth (t <sub>2</sub> )	69 mm

### Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	0.386 kg

### Certificates and Declarations

Declaration of Conformity - CE	2CDK400595D2705
Declaration of Conformity - UKCA	9AKK108467A5201

### Installation

Instructions and Manuals	2CDC002177D0202
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position	any

### Popular Downloads

Data Sheet, Technical Information	2CDC002177D0204
-----------------------------------	-----------------

### External Classifications and Standards

ETIM 9	EC000042 - Miniature circuit breaker (MCB)
ETIM 10	EC000042 - Miniature circuit breaker (MCB)
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4899 >> Miniature circuit breaker (MCB) screw-in model
Standards	CSA 22.2 No. 5 IEC/EN 60947-2 UL 489
Certification Agency	CSA EN IEC UL
Standardization Body	CSA EN IEC UL

### Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CCA880100R0001	CMS-100PS Sensor	CMS-100PS	1	piece
2CCA880101R0001	CMS-101PS Sensor	CMS-101PS	1	piece
2CCA880102R0001	CMS-102PS Sensor	CMS-102PS	1	piece
2CDS200914R0001	S2C-H6RU Auxiliary Contact 1CO, UL489	S2C-H6RU	1	piece
2CDS200924R0001	S2C-S6RU Signal Contact UL489	S2C-S6RU	1	piece
2CDS200908R0001	S2C-A1U Shunt Trip, 12...110V, UL489	S2C-A1U	1	piece
2CDS200908R0002	S2C-A2U Shunt Trip, 110...415V, UL489	S2C-A2U	1	piece

### Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs → SU200M

