



 PRODUCT-DETAILS

AF09ZB-30-01RT-21

AF09ZB-30-01RT-21 24-60V50/60HZ 20-60VDC Contactor



General Information

Extended Product Type	AF09ZB-30-01RT-21
Product ID	1SBL136060R2101
EAN	3471523127715
Catalog Description	AF09ZB-30-01RT-21 24-60V50/60HZ 20-60VDC Contactor

Long Description	<p>The AF09ZB-30-01RT-21 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and Ring-Tongue Terminals, controlling motors up to 4 kW / 400 V AC (AC-3) or 5 hp / 480 V UL and switching power circuits up to 25 A (AC-1) or 25 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (24-60 V 50/60 Hz and 20-60 V DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p>
------------------	--

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC100220C0201
Instructions and Manuals	1SBC101035M6801
Instructions and Manuals (Part 2)	1SAC200017M0002
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	45 mm
Product Net Depth / Length	77 mm
Product Net Height	86 mm
Product Net Weight	0.32 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	1
Number of Poles	3P
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1, IEC 60077-1 (applicable parts), IEC 60077-2 (applicable parts), EN 50155 (applicable parts), TR CU 001/2011, IEC 61373, For compliance confirmation on applicable parts based on your application and combination, please consult your ABB sales representatives.
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^{\circ}\text{C}$ 35 A acc. to IEC 60947-5-1, $\Theta = 40\text{ }^{\circ}\text{C}$ 16 A
Rated Operational Current AC-1 (I _e)	(690 V) 40 $^{\circ}\text{C}$ 25 A (690 V) 60 $^{\circ}\text{C}$ 25 A (690 V) 70 $^{\circ}\text{C}$ 22 A
Rated Operational Current AC-3 (I _e)	(415 V) 60 $^{\circ}\text{C}$ 9 A (440 V) 60 $^{\circ}\text{C}$ 9 A (500 V) 60 $^{\circ}\text{C}$ 9.5 A (690 V) 60 $^{\circ}\text{C}$ 7 A (380 / 400 V) 60 $^{\circ}\text{C}$ 9 A (220 / 230 / 240 V) 60 $^{\circ}\text{C}$ 9 A
Rated Operational Current AC-3e (I _e)	(415 V) 60 $^{\circ}\text{C}$ 9 A (440 V) 60 $^{\circ}\text{C}$ 9 A (500 V) 60 $^{\circ}\text{C}$ 9.5 A (690 V) 60 $^{\circ}\text{C}$ 7 A (380 / 400 V) 60 $^{\circ}\text{C}$ 9 A (220 / 230 / 240 V) 60 $^{\circ}\text{C}$ 9 A
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A

	(400 / 440 V) 3 A
Rated Operational Current DC-1 (I _e)	(110 V) 1-Pole, 40 °C 10 A
	(110 V) 1-Pole, 60 °C 10 A
	(110 V) 1-Pole, 70 °C 10 A
	(110 V) 2 Poles in Series, 40 °C 25 A
	(110 V) 2 Poles in Series, 60 °C 25 A
	(110 V) 2 Poles in Series, 70 °C 22 A
	(110 V) 3 Poles in Series, 40 °C 25 A
	(110 V) 3 Poles in Series, 60 °C 25 A
	(110 V) 3 Poles in Series, 70 °C 22 A
	(220 V) 2 Poles in Series, 40 °C 10 A
	(220 V) 2 Poles in Series, 60 °C 10 A
	(220 V) 2 Poles in Series, 70 °C 10 A
	(220 V) 3 Poles in Series, 40 °C 25 A
	(220 V) 3 Poles in Series, 60 °C 25 A
	(220 V) 3 Poles in Series, 70 °C 22 A
	(72 V) 1-Pole, 40 °C 25 A
	(72 V) 1-Pole, 60 °C 25 A
	(72 V) 1-Pole, 70 °C 22 A
	(72 V) 2 Poles in Series, 40 °C 25 A
	(72 V) 2 Poles in Series, 60 °C 25 A
(72 V) 2 Poles in Series, 70 °C 22 A	
(72 V) 3 Poles in Series, 40 °C 25 A	
(72 V) 3 Poles in Series, 60 °C 25 A	
(72 V) 3 Poles in Series, 70 °C 22 A	
Rated Operational Current DC-3 (I _e)	(110 V) 1-Pole, 40 °C 6 A
	(110 V) 1-Pole, 60 °C 6 A
	(110 V) 1-Pole, 70 °C 6 A
	(110 V) 2 Poles in Series, 40 °C 25 A
	(110 V) 2 Poles in Series, 60 °C 25 A
	(110 V) 2 Poles in Series, 70 °C 22 A
	(110 V) 3 Poles in Series, 40 °C 25 A
	(110 V) 3 Poles in Series, 60 °C 25 A
	(110 V) 3 Poles in Series, 70 °C 22 A
	(220 V) 2 Poles in Series, 40 °C 6 A
	(220 V) 2 Poles in Series, 60 °C 6 A
	(220 V) 2 Poles in Series, 70 °C 6 A
	(220 V) 3 Poles in Series, 40 °C 25 A
	(220 V) 3 Poles in Series, 60 °C 25 A
	(220 V) 3 Poles in Series, 70 °C 22 A
	(72 V) 1-Pole, 40 °C 25 A
	(72 V) 1-Pole, 60 °C 25 A
	(72 V) 1-Pole, 70 °C 22 A
	(72 V) 2 Poles in Series, 40 °C 25 A
	(72 V) 2 Poles in Series, 60 °C 25 A
(72 V) 2 Poles in Series, 70 °C 22 A	
(72 V) 3 Poles in Series, 40 °C 25 A	
(72 V) 3 Poles in Series, 60 °C 25 A	
(72 V) 3 Poles in Series, 70 °C 22 A	
Rated Operational Current DC-5 (I _e)	(110 V) 1-Pole, 40 °C 4 A
	(110 V) 1-Pole, 60 °C 4 A
	(110 V) 1-Pole, 70 °C 4 A
	(110 V) 2 Poles in Series, 40 °C 10 A
	(110 V) 2 Poles in Series, 60 °C 10 A
	(110 V) 2 Poles in Series, 70 °C 10 A
	(110 V) 3 Poles in Series, 40 °C 25 A
	(110 V) 3 Poles in Series, 60 °C 25 A
	(110 V) 3 Poles in Series, 70 °C 22 A
	(220 V) 2 Poles in Series, 40 °C 4 A
	(220 V) 2 Poles in Series, 60 °C 4 A
	(220 V) 2 Poles in Series, 70 °C 4 A
	(220 V) 3 Poles in Series, 40 °C 9 A
	(220 V) 3 Poles in Series, 60 °C 9 A
	(220 V) 3 Poles in Series, 70 °C 9 A
	(72 V) 1-Pole, 40 °C 9 A
	(72 V) 1-Pole, 60 °C 9 A
	(72 V) 1-Pole, 70 °C 9 A
	(72 V) 2 Poles in Series, 40 °C 25 A
	(72 V) 2 Poles in Series, 60 °C 25 A
(72 V) 2 Poles in Series, 70 °C 22 A	
(72 V) 3 Poles in Series, 40 °C 25 A	

	(72 V) 3 Poles in Series, 60 °C 25 A (72 V) 3 Poles in Series, 70 °C 22 A
Rated Operational Current DC-13 (I_e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Operational Power AC-3 (P_e)	(415 V) 4 kW (440 V) 4 kW (500 V) 5.5 kW (690 V) 5.5 kW (380 / 400 V) 4 kW (220 / 230 / 240 V) 2.2 kW
Rated Operational Power AC-3e (P_e)	(415 V) 4 kW (440 V) 4 kW (500 V) 5.5 kW (690 V) 5.5 kW (380 / 400 V) 4 kW (220 / 230 / 240 V) 2.2 kW
Rated Short-time Withstand Current Low Voltage (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A for 0.1 s 140 A for 1 s 100 A
Maximum Breaking Capacity	$\cos \phi=0.45$ ($\cos \phi=0.35$ for $I_e > 100$ A) at 440 V 250 A $\cos \phi=0.45$ ($\cos \phi=0.35$ for $I_e > 100$ A) at 690 V 106 A
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U_c)	50 Hz 24 ... 60 V 60 Hz 24 ... 60 V DC Operation 20 ... 60 V
Power Loss	at 6 A per Pole 0.1 W at Rated Operating Conditions AC-1 per Pole 0.8 W at Rated Operating Conditions AC-3 per Pole 0.1 W
Operate Time	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M4 Screws Placed Diagonally
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP10 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP10 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Tightening Torque	Auxiliary Circuit 1.2 N·m Control Circuit 1.2 N·m Main Circuit 1.5 N·m

Terminal Type	Ring-Tongue Terminals
Product Name	Block Contactor

Technical UL/CSA

NEMA Size	00
Continuous Current Rating NEMA	9 A
Horsepower Rating NEMA	(115 V AC) Single Phase 1/3 Hp (200 V AC) Three Phase 1-1/2 Hp (230 V AC) Single Phase 1 Hp (230 V AC) Three Phase 1-1/2 Hp (460 V AC) Three Phase 2 Hp (575 V AC) Three Phase 2 Hp
Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(600 V AC) 25 A
Horsepower Rating UL/CSA	(120 V AC) Single Phase 3/4 hp (200 ... 208 V AC) Three Phase 2 hp (220 ... 240 V AC) Three Phase 2 hp (240 V AC) Single Phase 1-1/2 hp (440 ... 480 V AC) Three Phase 5 hp (550 ... 600 V AC) Three Phase 7-1/2 hp
Tightening Torque UL/CSA	Auxiliary Circuit 11 in-lb Control Circuit 11 in-lb Main Circuit 13 in-lb
Full Load Amps Motor Use	(120 V AC) Single Phase 13.8 A (200 ... 208 V AC) Three Phase 7.8 A (220 ... 240 V AC) Three Phase 6.8 A (240 V AC) Single Phase 10 A (440 ... 480 V AC) Three Phase 7.6 A (550 ... 600 V AC) Three Phase 9 A

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible	Without Derating 3000 m
Shock and Vibration Withstand acc. to IEC 61373	Category 1, Class B
Pollution Degree	3

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Declaration	2CMT2021-006277
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	118ec3a2-cb15-40f1-a5a2-7c0a10686d9c China
Simplified SCIP	0000924c-8822-4e15-9e73-773a164a3220 Spain 16a4e03c-2ce1-4618-97ca-5c29c8eaa689 Greece 2e37b9e7-e4ea-4c69-8c6d-eb1ea955fb2d Germany 2fd86823-0471-4b5e-81c0-c4f2612b1d1e France

3713ddbc-62c0-4ba1-be5d-0ddea0570e0d Norway
 3a4beb59-fdcd-4854-8b38-cc0137fa8257 Poland
 3d2f28c4-1e3f-44aa-8840-d86776d0acf7 Belgium
 3f83c86b-7dad-44cb-b8c8-0de6a0b52afd Germany
 46e5ab7f-cc6e-45cd-a4d3-cb1a72cc50d6 Hungary
 4a58f5d5-8582-44b1-923b-e7081073b1d7 Poland
 4ceabe46-bb28-44db-b5ce-3c9e9a97eef0 Estonia
 4d2d44b8-0cb0-4840-ae5c-8da682a053ab Netherlands
 69d6fcc0-4d7d-439d-a669-80bb8d38ce33 Poland
 79ad3ef1-d3f7-4193-ad50-9ca65da46c2c Bulgaria
 824789ef-3383-4913-9bfc-c28639732c40 France
 83e71834-affb-42d2-bfd2-aab153edb20c Germany
 8449f29a-f481-4032-a50d-bb7f78b70a5c Germany
 86b9378a-3d82-4380-bb98-3aa2cc8e4efb Belgium
 8853eaf2-017f-4e28-9949-566047e5ba28 Czech Republic
 91c3bf8e-f65e-4879-adb4-ff2d7e53f87a Croatia
 a24b6155-72ba-40a2-a120-5b3f899613d4 Sweden
 bd0c2cdb-469f-45cf-a1eb-2b92b0d71dd4 Germany
 c66bb100-41c3-4e0c-9569-d01231725309 Denmark
 cc61cda1-b29a-422d-9557-97663b580b3c Finland
 de8486c7-788f-4a43-b029-cb27933bf4b9 Sweden
 e09c4785-82ec-48ad-9589-cfe704861ab5 Hungary
 f3c0589e-4244-4fd9-9baf-725b3f352f32 Portugal
 2CMT2023-006525

Toxic Substances
 Control Act - TSCA

WEEE B2C / B2B

Business To Business

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill
End Of Life Disassembling Instructions	1SBC101080M6801
Environmental Product Declaration - EPD	1SBD250584E3000
Improved Energy Efficiency for Customers	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 92.7 %

Certificates and Declarations

CB Certificate	CB_SE-117714
CCC Certificate	CCC_2024010304656669
CQC Certificate	CQC2010010304445624
Declaration of Conformity - CCC	2020980304001253
Declaration of Conformity - CE	1SBD250004U1000
Declaration of Conformity - UKCA	1SBD250035U1000
UL Listing Card	UL_E312527
UR Certificate	UL_20121122-E312527_9_5

Container Information

Package Level 1 Units	box 1 piece
-----------------------	-------------

Package Level 1 Width	87 mm
Package Level 1 Depth / Length	79 mm
Package Level 1 Height	47 mm
Package Level 1 Gross Weight	0.32 kg
Package Level 1 EAN	3471523127715

External Classifications and Standards

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4758 >> lec Contactors

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
1SBN010110R1010	CA4-10 Auxiliary Contact Block	CA4-10	1	piece
1SBN010110T1010	CA4-10-T Auxiliary Contact Block	CA4-10-T	1	piece
1SBN010110R1001	CA4-01 Auxiliary Contact Block	CA4-01	1	piece
1SBN010110T1001	CA4-01-T Auxiliary Contact Block	CA4-01-T	1	piece
1SBN010120R1011	CAL4-11 Auxiliary Contact Block	CAL4-11	1	piece
1SBN010120T1011	CAL4-11-T Auxiliary Contact Block	CAL4-11-T	1	piece
1SBN010140R1022	CA4-22E Auxiliary Contact Block	CA4-22E	1	piece
1SBN010140R1031	CA4-31E Auxiliary Contact Block	CA4-31E	1	piece
1SBN010140R1040	CA4-40E Auxiliary Contact Block	CA4-40E	1	piece
1SBN010140R1004	CA4-04E Auxiliary Contact Block	CA4-04E	1	piece
1SBN010140R1322	CA4-22U Auxiliary Contact Block	CA4-22U	1	piece
1SBN010140R1122	CA4-22M Auxiliary Contact Block	CA4-22M	1	piece
1SBN010151R1011	CAT4-11E Auxiliary Contact / Coil Terminal Block	CAT4-11E	1	piece
1SBN010140R1331	CA4-31U Auxiliary Contact Block	CA4-31U	1	piece
1SBN010140R1131	CA4-31M Auxiliary Contact Block	CA4-31M	1	piece
1SBN010151R1111	CAT4-11M Auxiliary Contact / Coil Terminal Block	CAT4-11M	1	piece
1SBN010140R1340	CA4-40U Auxiliary Contact Block	CA4-40U	1	piece
1SBN010140R1113	CA4-13M Auxiliary Contact Block	CA4-13M	1	piece
1SBN010151R1311	CAT4-11U Auxiliary Contact / Coil Terminal Block	CAT4-11U	1	piece
1SBN070156T1000	LDC4 Additional Coil Terminal Block	LDC4	1	piece
1SBN010140R1104	CA4-04M Auxiliary Contact Block	CA4-04M	1	piece
1SBN010134R1011	CAL4-11K Auxiliary Contact Block	CAL4-11K	1	piece
1SBN110108T1000	BX4 Protective Cover	BX4	1	piece
1SBN010146R1104	CA4-04MK Auxiliary Contact Block	CA4-04MK	1	piece
1SBN010146R1113	CA4-13MK Auxiliary Contact Block	CA4-13MK	1	piece
1SBN070159T1000	LDC4K Additional Coil Terminal Block	LDC4K	1	piece
1SBN010160R1001	CA4-01K Auxiliary Contact Block	CA4-01K	1	piece
1SBN010146R1022	CA4-22EK Auxiliary Contact Block	CA4-22EK	1	piece
1SBN010160R1010	CA4-10K Auxiliary Contact Block	CA4-10K	1	piece
1SBN010146R1122	CA4-22MK Auxiliary Contact Block	CA4-22MK	1	piece
1SBN010160T1001	CA4-01K-T Auxiliary Contact Block	CA4-01K-T	1	piece
1SBN010160T1010	CA4-10K-T Auxiliary Contact Block	CA4-10K-T	1	piece
1SBN010146R1031	CA4-31EK Auxiliary Contact Block	CA4-31EK	1	piece
1SBN010146R1131	CA4-31MK Auxiliary Contact Block	CA4-31MK	1	piece
1SBN010146R1040	CA4-40EK Auxiliary Contact Block	CA4-40EK	1	piece

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF09

