



---

**PRODUCT-DETAILS**

## **AF116-30-00B-33**

### **AF116-30-00B-33 Contactor**



---

**General Information**

Extended Product Type	AF116-30-00B-33
Product ID	1SFL427002R3300
EAN	7320500481011
Catalog Description	AF116-30-00B-33 Contactor
Long Description	<p>The AF116-30-00B-33 is a 3 pole - 690 V IEC or 600 V UL contactor with Main Circuit Bars, controlling motors up to 55 kW / 400 V AC (AC-3) or 75 hp / 480 V UL and switching power circuits up to 160 A (AC-1) or 160 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (100-250 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p>

---

**Ordering**

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

## Popular Downloads

EPLAN Data	9AAC174538_EPLAN
Data Sheet, Technical Information	1SBC100214C0202
Data Sheet, Technical Information (Part 2)	1SAC200017M0002
Instructions and Manuals	1SFC100003M0201
CAD Dimensional Drawing	2CDC001079B0201

## Dimensions

Product Net Width	90 mm
Product Net Depth / Length	142.5 mm
Product Net Height	150 mm
Product Net Weight	1.3 kg

## Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Number of Poles	3P
Rated Operational Voltage	Main Circuit 690 V
Rated Frequency (f)	Main Circuit 60 Hz
Conventional Free-air Thermal Current (I <sub>th</sub> )	acc. to IEC 60947-4-1, Open Contactors Θ = 40 °C 160 A
Rated Operational Current AC-1 (I <sub>e</sub> )	(690 V) 40 °C 160 A (690 V) 60 °C 145 A (690 V) 70 °C 130 A
Rated Operational Current AC-3 (I <sub>e</sub> )	(415 V) 55 °C 116 A (440 V) 55 °C 116 A (500 V) 55 °C 110 A (690 V) 55 °C 65 A (380 / 400 V) 55 °C 116 A (220 / 230 / 240 V) 55 °C 116 A
Rated Operational Current AC-3e (I <sub>e</sub> )	(415 V) 60 °C 116 A (440 V) 60 °C 116 A (500 V) 60 °C 110 A (690 V) 60 °C 65 A (380 / 400 V) 60 °C 116 A (220 / 230 / 240 V) 60 °C 116 A
Rated Operational Power AC-3 (P <sub>e</sub> )	(415 V) 55 kW (440 V) 75 kW (500 V) 75 kW (690 V) 55 kW (380 / 400 V) 55 kW (220 / 230 / 240 V) 30 kW
Rated Operational Power AC-3e (P <sub>e</sub> )	(415 V) 55 kW (440 V) 75 kW (500 V) 75 kW (690 V) 55 kW

		(380 / 400 V) 55 kW (220 / 230 / 240 V) 30 kW
Rated Breaking Capacity AC-3		8 x Ie AC-3
Rated Breaking Capacity AC-3e		8.5 x Ie AC-3e
Rated Making Capacity AC-3		10 x Ie AC-3
Rated Making Capacity AC-3e		12 x Ie AC-3e
Short-Circuit Protective Devices		gG Type Fuses 250 A
Rated Short-time Withstand Current Low Voltage (Icw)		at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 928 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 160 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 379 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1160 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 536 A
Rated Insulation Voltage (Ui)		acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (Uimp )		8 kV
Maximum Electrical Switching Frequency		(AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour
Mechanical Durability		5 million
Maximum Mechanical Switching Frequency		300 cycles per hour
Coil Operating Limits		(acc. to IEC 60947-4-1) Uc (at θ ≤ 70 °C)
Rated Control Circuit Voltage (Uc)		50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Coil Consumption		Holding at Max. Rated Control Circuit Voltage 50 Hz 30.7 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 30.7 V-A Holding at Max. Rated Control Circuit Voltage DC 2.8 V-A Holding at Max. Rated Control Circuit Voltage DC 2.8 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 220 V-A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 220 V-A Pull-in at Max. Rated Control Circuit Voltage DC 275 V-A Pull-in at Max. Rated Control Circuit Voltage DC 275 W
Power Loss		at Rated Operating Conditions per Pole 6 W
Operate Time		Between Coil De-energization and NO Contact Opening 37 ... 47 ms Between Coil Energization and NO Contact Closing 25 ... 55 ms
Degree of Protection		acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40
Terminal Type		Main Circuit: Bars
Product Name		Block Contactor

## Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 160 A
Horsepower Rating UL/CSA	(200 ... 208 V AC) Three Phase 15 Hp (200 V AC) Three Phase 30 hp (208 V AC) Three Phase 30 hp (220 ... 240 V AC) Three Phase 20 Hp (220 ... 240 V AC) Three Phase 40 hp (440 ... 480 V AC) Three Phase 40 Hp (440 ... 480 V AC) Three Phase 75 hp (550 ... 600 V AC) Three Phase 50 Hp (550 ... 600 V AC) Three Phase 100 hp

## Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 55 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m

## Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Declaration	2CMT2021-006277
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## ABB EcoSolutions

ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	Non-hazardous waste is sent to a landfill, where there is no alternative option available within 100km of a facility UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions	1SFC100112M0001
Environmental Product Declaration - EPD	1SFC100092D0201
Improved Energy Efficiency for Customers	Product Efficiency - Product requires less energy to operate compared to similar product on market or older products from the same line Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 87.8 %

## Certificates and Declarations

A2L Certificate – UL	9AKK108468A6693
ABS Certificate	14-LD1092198-PDA
BV Certificate	BV_36353_A0BV
CB Certificate	SEMKO_SE-70479M1
CCS Certificate	GB14T00030
CQC Certificate	CQC2013010304604055
Declaration of Conformity - CCC	2020980304001304
Declaration of Conformity - CE	2CMT2015-005439
Declaration of Conformity - UKCA	2CMT2020-006118
DNV Certificate	DNV_E-14043
LR Certificate	16-20064
PRS Certificate	TE_2092_880423_16

RINA Certificate	ELE060313XG_002
RMRS Certificate	9AKK107045A6978
UL Certificate	20120925-E36588
UL Listing Card	UL_E36588

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	207 mm
Package Level 1 Depth / Length	216 mm
Package Level 1 Height	150 mm
Package Level 1 Gross Weight	1.5 kg
Package Level 1 EAN	7320500481011

## External Classifications and Standards

Object Classification	Q
Code	
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4758 >> Iec Contactors

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
1SFN074207R1000	LW140 Terminal Enlargement	LW140	1	piece
1SFN074210R1000	LX140 Terminal Extension	LX140	1	piece
1SFN084206R1000	BEA140/XT2 Connection Set	BEA140/XT2	1	piece
1SFN084206R1001	BEA140/XT4 Connection Set	BEA140/XT4	1	piece
1SFN084211R1000	BER140-4 Connection Set	BER140-4	1	piece
1SFN084214R1000	BEP140-30 Connection Set	BEP140-30	1	piece
1SFN084214R2000	BEP140-40 Connection Set	BEP140-40	1	piece
1SFN010820R1011	CAL19-11 Auxiliary Contact Block	CAL19-11	1	piece
1SFN010820R3311	CAL19-11B Auxiliary Contact Block	CAL19-11B	1	piece
1SFN030300R1000	VM19 Mechanical Interlock Unit	VM19	1	piece
1SFN034403R1000	VM140/190 Mechanical Interlock Unit	VM140/190	1	piece
1SFN010832R1001	CEL19-01 Auxiliary Contact Block	CEL19-01	1	piece
1SFN010832R1010	CEL19-10 Auxiliary Contact Block	CEL19-10	1	piece
1SFN124203R1000	LT140-30L Terminal Shroud	LT140-30L	1	piece
1SFN084413R1000	BEY140-4 Connection Set	BEY140-4	1	piece
1SFN084813R1000	BEY190-4 Connection Set	BEY190-4	1	piece

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF116



ABB  
**Eco**  
Solutions™