





---

 PRODUCT-DETAILS

## AF12-30-10K-11

### AF12-30-10K-11 24-60V50/60HZ 20-60VDC Contactor




---

**General Information**

|                       |   |
|-----------------------|---|
| Extended Product Type | AF12-30-10K-11                                  |
| Product ID            | 1SBL157005R1110                                 |
| EAN                   | 3471523154315                                   |
| Catalog Description   | AF12-30-10K-11 24-60V50/60HZ 20-60VDC Contactor |

|                  |  |
|------------------|--|
| Long Description | <p>The AF12-30-10K-11 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and push-in spring terminals, controlling motors up to 5.5 kW / 400 V AC (AC-3) or 7-1/2 hp / 480 V UL and switching power circuits up to 28 A (AC-1) or 28 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (24-60 V 50/60 Hz and 20-60 V DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p> |
|------------------|--|

---

**Ordering**

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

### Popular Downloads

|                                   |                  |
|-----------------------------------|------------------|
| EPLAN Data                        | 9AAC159646_EPLAN |
| Data Sheet, Technical Information | 1SBC100214C0202  |
| Instructions and Manuals          | 1SBC101054M6801  |
| Instructions and Manuals (Part 2) | 1SAC200017M0002  |
| CAD Dimensional Drawing           | 2CDC001079B0201  |

### Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 45 mm    |
| Product Net Depth / Length | 77 mm    |
| Product Net Height         | 92.3 mm  |
| Product Net Weight         | 0.285 kg |

### Technical

|  |  |
|--|--|
| Number of Main Contacts NO                               | 3  |
| Number of Main Contacts NC                               | 0  |
| Number of Auxiliary Contacts NO                          | 1  |
| Number of Auxiliary Contacts NC                          | 0  |
| Number of Poles  | 3P   |
| Standards  | IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1  |
| Rated Operational Voltage                                | Auxiliary Circuit 690 V<br>Main Circuit 690 V  |
| Rated Frequency (f)                                      | Auxiliary Circuit 50 / 60 Hz<br>Control Circuit 50 / 60 Hz<br>Main Circuit 50 / 60 Hz  |
| Conventional Free-air Thermal Current (I <sub>th</sub> ) | acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^{\circ}\text{C}$ 35 A<br>acc. to IEC 60947-5-1, $\Theta = 40\text{ }^{\circ}\text{C}$ 16 A |
| Rated Operational Current AC-1 (I <sub>e</sub> )         | (690 V) 40 °C 28 A<br>(690 V) 60 °C 28 A<br>(690 V) 70 °C 24 A   |
| Rated Operational Current AC-3 (I <sub>e</sub> )         | (415 V) 60 °C 12 A<br>(440 V) 60 °C 12 A<br>(500 V) 60 °C 12.5 A<br>(690 V) 60 °C 9 A<br>(380 / 400 V) 60 °C 12 A<br>(220 / 230 / 240 V) 60 °C 12 A    |
| Rated Operational Current AC-3e (I <sub>e</sub> )        | (415 V) 60 °C 12 A<br>(440 V) 60 °C 12 A<br>(500 V) 60 °C 12.5 A<br>(690 V) 60 °C 9 A<br>(380 / 400 V) 60 °C 12 A<br>(220 / 230 / 240 V) 60 °C 12 A    |
| Rated Operational Current AC-15 (I <sub>e</sub> )        | (500 V) 2 A<br>(690 V) 2 A<br>(24 / 127 V) 6 A<br>(220 / 240 V) 4 A<br>(400 / 440 V) 3 A   |
| Rated Operational Current DC-1 (I <sub>e</sub> )         | (110 V) 1-Pole, 40 °C 15 A<br>(110 V) 1-Pole, 60 °C 15 A   |

(110 V) 1-Pole, 70 °C 15 A  
 (110 V) 2 Poles in Series, 40 °C 27 A  
 (110 V) 2 Poles in Series, 60 °C 27 A  
 (110 V) 2 Poles in Series, 70 °C 24 A  
 (110 V) 3 Poles in Series, 40 °C 27 A  
 (110 V) 3 Poles in Series, 60 °C 27 A  
 (110 V) 3 Poles in Series, 70 °C 24 A  
 (220 V) 2 Poles in Series, 40 °C 15 A  
 (220 V) 2 Poles in Series, 60 °C 15 A  
 (220 V) 2 Poles in Series, 70 °C 15 A  
 (220 V) 3 Poles in Series, 40 °C 27 A  
 (220 V) 3 Poles in Series, 60 °C 27 A  
 (220 V) 3 Poles in Series, 70 °C 24 A  
 (72 V) 1-Pole, 40 °C 27 A  
 (72 V) 1-Pole, 60 °C 27 A  
 (72 V) 1-Pole, 70 °C 24 A  
 (72 V) 2 Poles in Series, 40 °C 27 A  
 (72 V) 2 Poles in Series, 60 °C 27 A  
 (72 V) 2 Poles in Series, 70 °C 24 A  
 (72 V) 3 Poles in Series, 40 °C 27 A  
 (72 V) 3 Poles in Series, 60 °C 27 A  
 (72 V) 3 Poles in Series, 70 °C 24 A

Rated Operational  
 Current DC-3 (I<sub>e</sub>)

(110 V) 1-Pole, 40 °C 7 A  
 (110 V) 1-Pole, 60 °C 7 A  
 (110 V) 1-Pole, 70 °C 7 A  
 (110 V) 2 Poles in Series, 40 °C 27 A  
 (110 V) 2 Poles in Series, 60 °C 27 A  
 (110 V) 2 Poles in Series, 70 °C 24 A  
 (110 V) 3 Poles in Series, 40 °C 27 A  
 (110 V) 3 Poles in Series, 60 °C 27 A  
 (110 V) 3 Poles in Series, 70 °C 24 A  
 (220 V) 2 Poles in Series, 40 °C 7 A  
 (220 V) 2 Poles in Series, 60 °C 7 A  
 (220 V) 2 Poles in Series, 70 °C 7 A  
 (220 V) 3 Poles in Series, 40 °C 27 A  
 (220 V) 3 Poles in Series, 60 °C 27 A  
 (220 V) 3 Poles in Series, 70 °C 24 A  
 (72 V) 1-Pole, 40 °C 27 A  
 (72 V) 1-Pole, 60 °C 27 A  
 (72 V) 1-Pole, 70 °C 24 A  
 (72 V) 2 Poles in Series, 40 °C 27 A  
 (72 V) 2 Poles in Series, 60 °C 27 A  
 (72 V) 2 Poles in Series, 70 °C 24 A  
 (72 V) 3 Poles in Series, 40 °C 27 A  
 (72 V) 3 Poles in Series, 60 °C 27 A  
 (72 V) 3 Poles in Series, 70 °C 24 A

Rated Operational  
 Current DC-5 (I<sub>e</sub>)

(110 V) 1-Pole, 40 °C 4 A  
 (110 V) 1-Pole, 60 °C 4 A  
 (110 V) 1-Pole, 70 °C 4 A  
 (110 V) 2 Poles in Series, 40 °C 15 A  
 (110 V) 2 Poles in Series, 60 °C 15 A  
 (110 V) 2 Poles in Series, 70 °C 15 A  
 (110 V) 3 Poles in Series, 40 °C 27 A  
 (110 V) 3 Poles in Series, 60 °C 27 A  
 (110 V) 3 Poles in Series, 70 °C 24 A  
 (220 V) 2 Poles in Series, 40 °C 4 A  
 (220 V) 2 Poles in Series, 60 °C 4 A  
 (220 V) 2 Poles in Series, 70 °C 4 A  
 (220 V) 3 Poles in Series, 40 °C 12 A  
 (220 V) 3 Poles in Series, 60 °C 12 A  
 (220 V) 3 Poles in Series, 70 °C 12 A  
 (72 V) 1-Pole, 40 °C 12 A  
 (72 V) 1-Pole, 60 °C 12 A  
 (72 V) 1-Pole, 70 °C 12 A  
 (72 V) 2 Poles in Series, 40 °C 27 A  
 (72 V) 2 Poles in Series, 60 °C 27 A  
 (72 V) 2 Poles in Series, 70 °C 24 A  
 (72 V) 3 Poles in Series, 40 °C 27 A  
 (72 V) 3 Poles in Series, 60 °C 27 A  
 (72 V) 3 Poles in Series, 70 °C 24 A

Rated Operational

(24 V) 6 A / 144 W

|   |   |
|---|---|
| Current DC-13 ( $I_e$ )                                     | (48 V) 2.8 A / 134 W<br>(72 V) 1 A / 72 W<br>(110 V) 0.55 A / 60 W<br>(125 V) 0.55 A / 69 W<br>(220 V) 0.27 A / 60 W<br>(250 V) 0.27 A / 68 W<br>(400 V) 0.15 A / 60 W<br>(500 V) 0.13 A / 65 W<br>(600 V) 0.1 A / 60 W   |
| Rated Operational Power AC-3 ( $P_e$ )                      | (415 V) 5.5 kW<br>(440 V) 5.5 kW<br>(500 V) 7.5 kW<br>(690 V) 7.5 kW<br>(380 / 400 V) 5.5 kW<br>(220 / 230 / 240 V) 3 kW  |
| Rated Operational Power AC-3e ( $P_e$ )                     | (415 V) 5.5 kW<br>(440 V) 5.5 kW<br>(500 V) 7.5 kW<br>(690 V) 7.5 kW<br>(380 / 400 V) 5.5 kW<br>(220 / 230 / 240 V) 3 kW  |
| Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ ) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A<br>for 0.1 s 140 A<br>for 1 s 100 A |
| Maximum Breaking Capacity                                   | cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 250 A<br>cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 90 A   |
| Rated Insulation Voltage ( $U_i$ )                          | acc. to IEC 60947-4-1 690 V<br>acc. to IEC 60947-5-1 690 V<br>acc. to UL/CSA 600 V  |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 6 kV  |
| Maximum Electrical Switching Frequency                      | (AC-1) 600 cycles per hour<br>(AC-15) 1200 cycles per hour<br>(AC-2 / AC-4) 300 cycles per hour<br>(AC-3) 1200 cycles per hour<br>(DC-13) 900 cycles per hour   |
| Maximum Mechanical Switching Frequency                      | 3600 cycles per hour  |
| Rated Control Circuit Voltage ( $U_c$ )                     | 50 Hz 24 ... 60 V<br>60 Hz 24 ... 60 V<br>DC Operation 20 ... 60 V  |
| Power Loss  | at 6 A per Pole 0.1 W<br>at Rated Operating Conditions AC-1 per Pole 1.43 W<br>at Rated Operating Conditions AC-3 per Pole 0.26 W   |
| Operate Time  | Between Coil De-energization and NC Contact Closing 13 ... 98 ms<br>Between Coil De-energization and NO Contact Opening 11 ... 95 ms<br>Between Coil Energization and NC Contact Opening 38 ... 90 ms<br>Between Coil Energization and NO Contact Closing 40 ... 95 ms  |
| Mounting on DIN Rail  | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715  |
| Mounting by Screws (not supplied)                           | 2 x M4 Screws Placed Diagonally   |
| Connecting Capacity Main Circuit                            | Flexible with Ferrule 1/2x 0.5 ... 4 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.5 ... 4 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.5 ... 2.5 mm <sup>2</sup><br>Flexible 1/2x 0.5 ... 4 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup><br>Rigid Stranded 1/2x 4 ... 6 mm <sup>2</sup>  |
| Connecting Capacity Auxiliary Circuit                       | Flexible with Ferrule 1/2x 0.5 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1/2x 0.5 ... 1.5 mm <sup>2</sup><br>Flexible 1/2x 0.5 ... 2.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup>   |

|                                     |   |
|-------------------------------------|---|
| Connecting Capacity Control Circuit | Flexible with Ferrule 1/2x 0.5 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1/2x 0.5 ... 1.5 mm <sup>2</sup><br>Flexible 1/2x 0.5 ... 2.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup> |
| Wire Stripping Length               | Auxiliary Circuit 10 mm<br>Control Circuit 10 mm<br>Main Circuit 10 mm  |
| Degree of Protection                | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20                     |
| Terminal Type                       | Push-in Spring Terminals  |
| Product Name                        | Block Contactor   |

**Technical UL/CSA**

|  |   |
|--|---|
| NEMA Size                                    | 0   |
| Continuous Current Rating NEMA               | 18 A  |
| Horsepower Rating NEMA                       | (115 V AC) Single Phase 1 Hp<br>(200 V AC) Three Phase 3 Hp<br>(230 V AC) Single Phase 2 Hp<br>(230 V AC) Three Phase 3 Hp<br>(460 V AC) Three Phase 5 Hp<br>(575 V AC) Three Phase 5 Hp                                      |
| Maximum Operating Voltage UL/CSA             | Main Circuit 600 V  |
| General Use Rating UL/CSA                    | (600 V AC) 28 A   |
| Horsepower Rating UL/CSA                     | (120 V AC) Single Phase 1 hp<br>(200 ... 208 V AC) Three Phase 3 hp<br>(220 ... 240 V AC) Three Phase 3 hp<br>(240 V AC) Single Phase 2 hp<br>(440 ... 480 V AC) Three Phase 7-1/2 hp<br>(550 ... 600 V AC) Three Phase 10 hp |
| Connecting Capacity Main Circuit UL/CSA      | Rigid Solid 1/2x 18-14 AWG<br>Rigid Stranded 1/2x 18-10 AWG   |
| Connecting Capacity Auxiliary Circuit UL/CSA | Rigid Solid 1/2x 18-14 AWG  |
| Connecting Capacity Control Circuit UL/CSA   | Rigid Solid 1/2x 18-14 AWG  |
| Full Load Amps Motor Use                     | (120 V AC) Single Phase 16 A<br>(200 ... 208 V AC) Three Phase 11 A<br>(220 ... 240 V AC) Three Phase 9.6 A<br>(240 V AC) Single Phase 12 A<br>(440 ... 480 V AC) Three Phase 11 A<br>(550 ... 600 V AC) Three Phase 11 A     |

**Environmental**

|  |   |
|--|---|
| Ambient Air Temperature                | Close to Contactor without Thermal O/L Relay -40 ... 70 °C<br>Close to Contactor for Storage -60 ... +80 °C |
| Climatic Withstand                     | Category B according to IEC 60947-1 Annex Q   |
| Maximum Operating Altitude Permissible | Without Derating 3000 m   |
| Resistance to Vibrations               | 4g Closed Position & 2g Open position 5 ... 300 Hz  |
| Pollution Degree                       | 3   |

**Material Compliance**

|                   |                 |
|-------------------|-----------------|
| Conflict Minerals | 9AKK108467A5658 |
|-------------------|-----------------|

|                                     |  |
|-------------------------------------|--|
| Reporting Template (CMRT)           |  |
| REACH Declaration                   | 2CMT2021-006202  |
| RoHS Declaration                    | 2CMT2021-006277  |
| RoHS Information                    | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 2CMT2023-006525  |
| WEEE B2C / B2B                      | Business To Business   |
| WEEE Category                       | 5. Small Equipment (No External Dimension More Than 50 cm)             |

### ABB EcoSolutions

|   |  |
|---|--|
| ABB EcoSolutions                                  | Yes  |
| ABB Site Meeting Group Waste To Landfill Target   | No non-hazardous waste is sent to a landfill   |
| End Of Life Disassembling Instructions            | 1SBC101080M6801  |
| Environmental Product Declaration - EPD           | 1SBD250584E3000  |
| Improved Energy Efficiency for Customers          | Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line |
| Recyclability Rate of the Product acc. to EN45555 | Design for Closing Resource Loops - Standard EN45555 - 92.7 %  |

### Certificates and Declarations

|                                  |  |
|----------------------------------|--|
| ABS Certificate                  | ABS_20-2060694-PDA                         |
| BV Certificate                   | BV_2634H24898C1                            |
| CB Certificate                   | CB_SE-117714                               |
| CCC Certificate                  | CCC_2024010304656669                       |
| CQC Certificate                  | CQC2010010304445624<br>CQC2020010304298240 |
| Declaration of Conformity - CCC  | 2020980304001253<br>2020980304001082       |
| Declaration of Conformity - CE   | 1SBD250000U1000                            |
| Declaration of Conformity - UKCA | 1SBD250031U1000                            |
| DNV Certificate                  | DNV_TAE00001AF-4                           |
| LR Certificate                   | LRS_LR23403517TA-02                        |
| RINA Certificate                 | RINA_ELE142224XG                           |
| RMRS Certificate                 | RMRS_1802705280                            |
| UL Certificate                   | UL-US-2150887-5<br>UL-CA-2142658-5         |

### Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 93 mm         |
| Package Level 1 Depth / Length | 86 mm         |
| Package Level 1 Height         | 45 mm         |
| Package Level 1 Gross Weight   | 0.3 kg        |
| Package Level 1 EAN            | 3471523154315 |

## External Classifications and Standards

|                                    |  |
|------------------------------------|--|
| Object Classification Code         | Q  |
| ETIM 7                             | EC000066 - Power contactor, AC switching |
| ETIM 8                             | EC000066 - Power contactor, AC switching |
| ETIM 9                             | EC000066 - Power contactor, AC switching |
| eClass                             | V11.0 : 27371003                         |
| UNSPSC                             | 39121529                                 |
| IDEA Granular Category Code (IGCC) | 4758 >> Iec Contactors                   |
| E-Number (Finland)                 | 3707865                                  |
| E-Number (Sweden)                  | 3210589                                  |

## Accessories

| Identifier      | Description                                      | Type       | Quantity | Unit Of Measure |
|-----------------|--|------------|----------|-----------------|
| 1SBN010015R1001 | CE5-01D0.1 Auxiliary Contact Block               | CE5-01D0.1 | 1        | piece           |
| 1SBN010015R1010 | CE5-10D0.1 Auxiliary Contact Block               | CE5-10D0.1 | 1        | piece           |
| 1SBN010016R1001 | CE5-01W0.1 Auxiliary Contact Block               | CE5-01W0.1 | 1        | piece           |
| 1SBN010016R1010 | CE5-10W0.1 Auxiliary Contact Block               | CE5-10W0.1 | 1        | piece           |
| 1SBN010017R1001 | CE5-01D2 Auxiliary Contact Block                 | CE5-01D2   | 1        | piece           |
| 1SBN010017R1010 | CE5-10D2 Auxiliary Contact Block                 | CE5-10D2   | 1        | piece           |
| 1SBN010018R1001 | CE5-01W2 Auxiliary Contact Block                 | CE5-01W2   | 1        | piece           |
| 1SBN010018R1010 | CE5-10W2 Auxiliary Contact Block                 | CE5-10W2   | 1        | piece           |
| 1SBN010110R1010 | CA4-10 Auxiliary Contact Block                   | CA4-10     | 1        | piece           |
| 1SBN010110T1010 | CA4-10-T Auxiliary Contact Block                 | CA4-10-T   | 1        | piece           |
| 1SBN010110R1001 | CA4-01 Auxiliary Contact Block                   | CA4-01     | 1        | piece           |
| 1SBN010110T1001 | CA4-01-T Auxiliary Contact Block                 | CA4-01-T   | 1        | piece           |
| 1SBN010111R1010 | CC4-10 Leading Auxiliary Contact Block           | CC4-10     | 1        | piece           |
| 1SBN010111R1001 | CC4-01 Lagging Auxiliary Contact Block           | CC4-01     | 1        | piece           |
| 1SBN010120R1011 | CAL4-11 Auxiliary Contact Block                  | CAL4-11    | 1        | piece           |
| 1SBN010120T1011 | CAL4-11-T Auxiliary Contact Block                | CAL4-11-T  | 1        | piece           |
| 1SBN010140R1322 | CA4-22U Auxiliary Contact Block                  | CA4-22U    | 1        | piece           |
| 1SBN010140R1122 | CA4-22M Auxiliary Contact Block                  | CA4-22M    | 1        | piece           |
| 1SBN010151R1011 | CAT4-11E Auxiliary Contact / Coil Terminal Block | CAT4-11E   | 1        | piece           |
| 1SBN010140R1331 | CA4-31U Auxiliary Contact Block                  | CA4-31U    | 1        | piece           |
| 1SBN010140R1131 | CA4-31M Auxiliary Contact Block                  | CA4-31M    | 1        | piece           |
| 1SBN010151R1111 | CAT4-11M Auxiliary Contact / Coil Terminal Block | CAT4-11M   | 1        | piece           |
| 1SBN010140R1340 | CA4-40U Auxiliary Contact Block                  | CA4-40U    | 1        | piece           |
| 1SBN010140R1113 | CA4-13M Auxiliary Contact Block                  | CA4-13M    | 1        | piece           |
| 1SBN010151R1311 | CAT4-11U Auxiliary Contact / Coil Terminal Block | CAT4-11U   | 1        | piece           |
| 1SBN070156T1000 | LDC4 Additional Coil Terminal Block              | LDC4       | 1        | piece           |
| 1SBN010140R1104 | CA4-04M Auxiliary Contact Block                  | CA4-04M    | 1        | piece           |
| 1SBN020112R1000 | TEF4-ON Frontal Electronic Timer                 | TEF4-ON    | 1        | piece           |
| 1SBN020113R1000 | TEF4S-ON Frontal Electronic Timer                | TEF4S-ON   | 1        | piece           |
| 1SBN010134R1011 | CAL4-11K Auxiliary Contact Block                 | CAL4-11K   | 1        | piece           |
| 1SBN020114R1000 | TEF4-OFF Frontal Electronic Timer                | TEF4-OFF   | 1        | piece           |
| 1SBN020115R1000 | TEF4S-OFF Frontal Electronic Timer               | TEF4S-OFF  | 1        | piece           |
| 1SBN071303T1000 | LY16-4 Connecting Strip                          | LY16-4     | 1        | piece           |

|                 |  |           |   |       |
|-----------------|--|-----------|---|-------|
| 1SBN071305R1000 | LF16-4 Connecting Strip                            | LF16-4    | 1 | piece |
| 1SBN110108T1000 | BX4 Protective Cover                               | BX4       | 1 | piece |
| 1SBN040100R1011 | WA4-11 24-60V50/60HZ-DC Mechanical Latching Unit   | WA4-11    | 1 | piece |
| 1SBN040100R1014 | WA4-14 250-500V50/60HZ-DC Mechanical Latching Unit | WA4-14    | 1 | piece |
| 1SBN040100R1010 | WA4-10 24VDC Mechanical Latching Unit              | WA4-10    | 1 | piece |
| 1SBN040100R1012 | WA4-12 48-130V50/60HZ-DC Mechanical Latching Unit  | WA4-12    | 1 | piece |
| 1SBN060100R1000 | RA4 Interface Relay                                | RA4       | 1 | piece |
| 1SBN010146R1104 | CA4-04MK Auxiliary Contact Block                   | CA4-04MK  | 1 | piece |
| 1SBN040100R1013 | WA4-13 100-250V50/60HZ-DC Mechanical Latching Unit | WA4-13    | 1 | piece |
| 1SBN010146R1113 | CA4-13MK Auxiliary Contact Block                   | CA4-13MK  | 1 | piece |
| 1SBN070159T1000 | LDC4K Additional Coil Terminal Block               | LDC4K     | 1 | piece |
| 1SBN010160R1001 | CA4-01K Auxiliary Contact Block                    | CA4-01K   | 1 | piece |
| 1SBN010160R1010 | CA4-10K Auxiliary Contact Block                    | CA4-10K   | 1 | piece |
| 1SBN010146R1122 | CA4-22MK Auxiliary Contact Block                   | CA4-22MK  | 1 | piece |
| 1SBN010160T1001 | CA4-01K-T Auxiliary Contact Block                  | CA4-01K-T | 1 | piece |
| 1SBN010160T1010 | CA4-10K-T Auxiliary Contact Block                  | CA4-10K-T | 1 | piece |
| 1SBN010146R1131 | CA4-31MK Auxiliary Contact Block                   | CA4-31MK  | 1 | piece |

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF12

