

PRODUCT-DETAILS

# DP50C3P-1

## DP50C3P-1 Contactor



### General Information

Extended Product Type	DP50C3P-1
Product ID	1SBX105300R1200
EAN	0804325552219
Catalog Description	DP50C3P-1 Contactor
Long Description	DP50C3P-1 DP contactor provide outstanding performance in various HVAC application and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

### Dimensions

Product Net Width	70 mm
Product Net Depth / Length	83.7 mm
Product Net Height	95.8 mm
Product Net Weight	0.64 kg

### Technical

Number of Main Contacts NO	3
Standards	IEC 60947-4-1 UL 508
Rated Frequency (f)	Control Circuit 50 Hz Control Circuit 60 Hz
Rated Control Supply Voltage (U <sub>s</sub> )	120 V AC

---

## Environmental

RoHS Status	No declaration needed
-------------	-----------------------

---

## Technical UL/CSA

Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 3 Hp (208 V AC) Three Phase 15 Hp (220 ... 240 V AC) Single Phase 7.5 Hp (220 ... 240 V AC) Three Phase 15 Hp (440 ... 480 V AC) Three Phase 25 Hp (550 ... 600 V AC) Three Phase 25 Hp
Full Load Amps AC Resistance (Heating)	(600 V AC) 65 A
Full Load Amps Motor Use	50 A
Locked Rotor Amps	(480 V AC) 250 A (600 V AC) 200 A

---

## Certificates and Declarations (Document Number)

cUL Certificate	cUL_E224401
Declaration of Conformity - CE	NoDecNee
RoHS Information	NoDecNee
UL Certificate	UL_E224401

---

## Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	76.2 mm
Package Level 1 Depth / Length	88.9 mm
Package Level 1 Height	101.6 mm

---

## Classifications

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
UNSPSC	39121529

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Definite Purpose Contactors

