

N-Series

CIRCUIT BREAKER

The high-performance N-Series hydraulic-magnetic circuit breaker is ideally suited for the rigors and confined spaces of telecom and datacom power distribution units and rack systems. Its innovative, low profile design features easily accessible load and line terminals and sliding barriers for effortless installation. The optional current transformer allows for remote outlet metering and monitoring of power usage thus facilitating load adjustments and maximizing efficiency. A patent pending, flush-rocker actuator and push-to-reset guard offer additional protection against accidental switching.



Resources:

[Download 3D CAD Files](#)

[IGS >](#)

[STP >](#)

[Watch Product Video](#)



Product Highlights:

- ♦ 240 VAC, 277 VAC, 120/240 VAC
- ♦ UL 489 Compliant Sliding Terminal Barriers
- ♦ 22,000 Amps Max Interrupting Capacity
- ♦ 1 – 30 Amps Current Rating
- ♦ Optional Current Transformer
- ♦ EN60947-2 Certified

Typical Applications:

- ♦ Telecom/Datacom
 - PDU's
 - Data Servers
 - Data Storage



Carling Technologies™

Innovative Designs. Powerful Solutions.

Carling Technologies, Inc.
60 Johnson Avenue, Plainville, CT 06062
Email: sales@carlingtech.com
Application Support: team2@carlingtech.com
Phone: 860.793.9281 Fax: 860.793.9231

www.carlingtech.com

N-Series

DESIGN FEATURES

CURRENT TRANSFORMER


Remote current sensing via molex connector

UPPER ARC RUNNER


Optional, for 277 VAC rated breakers

GRIDS (5x)

Arc deionizing splitter plates that increase arc voltage for quick interrupt



SLIDING TERMINAL BARRIERS



Electrical Tables




Table 1: Voltage and Current Ratings

N-SERIES TABLE 1: ELECTRICAL RATINGS						
VOLTAGE	CURRENT (AMPS)	NUMBER OF POLES	INTERRUPT CAPACITY (AMPS)			
			UL 489		EN60947-2 (Ics & Icu)	
			1-20 A	21-30 A	1-20 A	21-30 A
120/240 VAC	1 - 30	2	10000	5000	5000	5000
240 VAC	1 - 20	1	22000	N/A	5000	5000
277 VAC	1 - 20	1	10000	N/A	N/A	N/A

Table 2: Time Delay

N-SERIES TABLE 2: TIME DELAY OPTIONS			
DELAY CURVE NUMBER	VOLTAGE	DESCRIPTION	
21	50/60 Hz	Ultrashort	
22	50/60 Hz	Short	
24	50/60 Hz	Medium	
26	50/60 Hz	Long	
42	50/60 Hz	Hi-inrush, Short	
44	50/60 Hz	Hi-inrush, Medium	
46	50/60 Hz	Hi-inrush, Long	

Electrical: Impedance / Resistance



CURRENT (AMPS)	TOLERANCE (%)
0.10 - 5.0	± 15
5.1 - 30.0	± 25

*Manufacturer reserves the right to change product specification without prior notice.

Electrical

Current Metering


Integrated current transformer.
Measurement range: 1-30 Amps.
Voltage output: 10mV per Amp
according to the formula below:
 $2 \text{ (Amp)} \leq I \leq 30 \text{ (Amp)}$

$$V = 0.01 \cdot I \pm 2\%$$

$$\left| \frac{\frac{V}{I} - \frac{V_{10}}{I_{10}}}{\frac{V_{10}}{I_{10}}} \right| \leq 0.85\%$$

Where V=CT output in volts
 V_{10} =CT output in volts with
 $I=I_{10}=10 \text{ (A)}$; I =primary current in
amperage (50/60 Hz). Phase shift
between primary current and CT
output is $0.25 \pm 0.25^\circ$. Maximum
crest factor of primary current is 1.73.
R1 shall be integrated in the breaker.
R2 and R3 are provided by end user
and external to the breaker.
Connection: below Load Terminal.
2-pin connector, Molex 35362-0250.
Mating Connector housing – Molex
PN35507-0200.

(Current metering is available on AC
rated devices only)



Dielectric Strength

UL, CSA-1960V 50/60 Hz for one
minute between all electrically
isolated terminals. Comply
with the 8mm spacing and 3750V
50/60 Hz dielectric requirements
from hazardous voltage to
operator accessible surfaces and
between main circuits of adjacent
poles per Publications EN 60950
and VDE 0805

Insulation Resistance Overload

Minimum of 100 Megohms @ 500VDC
50 operations @ 600% of rated current
for AC rated devices

Interrupt Capacity

See table 1

Mechanical

Endurance

10,000 "On-Off" operations @ 6 per
minute; with rated current & voltage

Trip Free

Trips on overload even when
actuator is forcibly held in the "On"
position

Trip Indication

The operating actuator moves
positively to the "Off" position
when an overload causes the
breaker to trip

Environmental

Environmental Operating Temperature Vibration

MIL-PRF-55629 and MIL-STD-202G
-40°C to +85°C
Withstands 0.06" excursion
from 10-55 Hz and 10Gs 55-500 Hz
at rated current per MIL-PRF-55629
and MIL-STD-202G, Method 204D,
Test Condition A. Instantaneous and
ultra-short curves tested at 90% of
rated current

Shock

Withstands 50 Gs, 6 ms saw tooth
while carrying rated current per
MIL-PRF-55629 and MIL-STD-202G,
Method 213B, test condition "I".
Instantaneous and ultra short curves
tested at 90% of rated current

Thermal Shock

MIL-PRF-55629 and MIL-STD-202G,
Method 107G, Condition A (5-cycles
at -55°C to +25°C to +85°C to +25°C)

Moisture Resistance

MIL-PRF-55629 and MIL-STD-202G,
Method 106G, i.e., Ten 24-hour
cycles at +25°C to +65°C, 80-98% RH
Method 101, Condition A (90-95%
RH @ 5% NaCl Solution, 96hrs)

Salt Spray

Physical

Number of Poles Termination

1 - 2 poles
Wire ready and touch proof wire
clamp (See Figure 1). Accepts up
to (2) #10 AWG wires per terminal.
Designed for use with solid,
stranded and flexible stranded
wires, with or without ferrule or pin
terminals. Also accepts straight fork
and flanged fork terminals.

Termination Torque Termination Barrier

15-20 in-lbs (Line & Load terminals)
Integral sliding barrier to comply
with spacing requirements
(See figure 1)

Mounting

Threaded Insert: #6-32 UNC-2B, or
M3X0.5-6H B ISO (2 per Pole)

Insert Termination Torque Actuator

7-9 in-lbs
Rocker, with or without guard
(See figures 1, 2, and 4)

Internal Circuit Config. Materials

Series Trip
Housing - Glass Filled Polyester
Rocker - Nylon
Line/Load Terminals - Copper Alloy;
Bright Acid Tin Plated
~107 grams (~3.76 ounces) per pole
Housing - Black. Rocker - Several
(See ordering scheme for colors)

Agency Approvals

UL 489, cUL, TUV EN60947-2

N	1	1	-	B	0	-	24	-	620	-	1	2	1	-	D	G
1 Series	2 Actuator	3 Poles		4 Circuit	5 Current Metering		6 Frequency & Delay		7 Current Rating		8 Terminal	9 Actuator Color & Legend	10 Mounting		11 Rating	12 Agency Approval

1 SERIES**N** N-Series Circuit Breaker**2 ACTUATOR**

- 1** Single Color Low Profile Rocker, Vertical Legend
- 2** Single Color Low Profile Rocker, Horizontal Legend
- 3** Single Color Push To Reset Low Profile Rocker, Vertical Legend
- 4** Single Color Push To Reset Low Profile Rocker, Horizontal Legend

3 POLES

- 1** One
- 2** Two

4 CIRCUIT**B** Series Trip (current)**5 CURRENT METERING**

- 0** Without Current Transformer
- 1** Integrated Current Transformer, 1 per unit ¹
- 2** Integrated Current Transformer, 1 per pole

6 FREQUENCY & DELAY

- | | |
|--------------------------------|--------------------------------------|
| 21 50/60 Hz Ultra Short | 42 50/60 Hz Short, HI-Inrush |
| 22 50/60 Hz Short | 44 50/60 Hz Medium, HI-Inrush |
| 24 50/60 Hz Medium | 46 50/60 Hz Long, HI-Inrush |
| 26 50/60 Hz Long | |

7 CURRENT RATING (AMPERES)

CODE	AMPERES				
410	1.00	440	4.00	490	9.00
512	1.25	445	4.50	495	9.50
415	1.50	450	5.00	610	10.00
517	1.75	455	5.50	710	10.50
420	2.00	460	6.00	611	11.00
522	2.25	465	6.50	711	11.50
425	2.50	470	7.00	612	12.00
527	2.75	475	7.50	712	12.50
430	3.00	480	8.00	613	13.00
435	3.50	485	8.50	614	14.00
				615	15.00
				616	16.00
				617	17.00
				618	18.00
				620	20.00
				622	22.00
				624	24.00
				625	25.00
				630	30.00

8 TERMINAL

- 1** Screw Terminal

9 ACTUATOR COLOR & LEGEND

Actuator Color	I-O	ON-OFF	Dual	Legend Color
White	A	B	1	Black
Black	C	D	2	White
Red	F	G	3	White
Green	H	J	4	White
Blue	K	L	5	White
Yellow	M	N	6	Black
Gray	P	Q	7	Black
Orange	R	S	8	Black

10 MOUNTING

- 1** 6-32 x .195 inches Threaded Inserts
- 2** ISO M3 x 5 mm Threaded Inserts

11 APPLICATION RATING

- C** 120/240 VAC (2 Pole only)
- D** 240 VAC ²
- F** 277 VAC ³

12 AGENCY APPROVAL


- A** Without Approvals
- G** UL 489 Listed
- 3** UL 489 Listed, TUV Certified ⁴

Notes:

- ¹ On multi pole units one current transformer is supplied on the actuator pole
- ² Available up to 20 amps
- ³ Voltage rating F only available as a 1 pole device at 20 amps maximum
- ⁴ TUV approval requires dual (I-O, ON-OFF) markings

Dimensional Specifications: in. [mm]

Figure 1. N-Series 1-Pole Construction



Notes:

- 1 All dimensions are in inches [millimeters].
2 Tolerance $\pm .020$ [.51] unless otherwise specified.

Dimensional Specifications: in. [mm]

Figure 2. N-Series 2-Pole Construction





Figure 3. N-Series Panel Cut-Out



Notes:

- 1 All dimensions are in inches [millimeters].
- 2 Tolerance ± 0.020 [51] unless otherwise specified.

Authorized Sales Representatives

Click on the group name on the map below to find your local representative or visit www.carlingtech.com/findarep.



About Carling

Founded in 1920, Carling Technologies is a leading manufacturer of electrical and electronic switches and assemblies, circuit breakers, electronic controls, power distribution units, and multiplexed power distribution systems. With four ISO registered manufacturing facilities and technical sales offices worldwide, Carling Technologies Sales, Service and Engineering teams do much more than manufacture electrical components, they engineer powerful solutions! To learn more about Carling please visit www.carlingtech.com/company-profile.

To view all of Carling's environmental, quality, health & safety certifications please visit www.carlingtech.com/environmental-certifications

Worldwide Headquarters

Carling Technologies, Inc.
60 Johnson Avenue, Plainville, CT 06062
Phone: 860.793.9281 **Fax:** 860.793.9231
Email: sales@carlingtech.com

Northern Region Sales Office: nrsm@carlingtech.com
Southeast Region Sales Office: sersm@carlingtech.com
Midwest Region Sales Office: mrsm@carlingtech.com
West Region Sales Office: wrsm@carlingtech.com
Latin America Sales Office: larsm@carlingtech.com

Asia-Pacific Headquarters

Carling Technologies, Asia-Pacific Ltd.,
Kowloon, Hong Kong
Phone: Int + 852-2737-2277 **Fax:** Int + 852-2736-9332
Email: sales@carlingtech.com.hk

Shenzhen, China: shenzhen@carlingtech.com
Shanghai, China: shanghai@carlingtech.com
Pune, India: india@carlingtech.com
Kaohsiung, Taiwan: taiwan@carlingtech.com
Yokohama, Japan: japan@carlingtech.com

Europe | Middle East | Africa Headquarters

Carling Technologies LTD
4 Airport Business Park, Exeter Airport,
Clyst Honiton, Exeter, Devon, EX5 2UL, UK
Phone: Int + 44 1392.364422 **Fax:** Int + 44 1392.364477
Email: ltd.sales@carlingtech.com

Germany: gmbh@carlingtech.com
France: sas@carlingtech.com



Carling Technologies™
Innovative Designs. Powerful Solutions.