


**Proximity Switch - Reed Switch based - Rectangular - Change Over Contacts**  
**Part Number : LMPSC 130/30      Suggested Magnet: LMPSM**  
**Product Data Sheet**

**PICTURE**



**DIMENSIONS**



**SPECIFICATION**

Contact Form / Style	Change Over
Switching Voltage	100 Vac
Switching Current	0.5 A
Switching Capacity (Resistive)	5 VA
Switching Distance	5.0 mm Minimum
Operating Temperature - Continuous	-20°C +70°C
Operating Temperature - Intermittent	-25°C +70°C
Storage temperature	-25°C +70°C
Case Material	ABS
Cable	White/Brown/Green 7/0.2mm² PVC 70°C

**Applications Include**

- Position and limit sensing.
- Linear actuators.
- Security system switch.
- Door Switch.

**Options**

- Higher Specification switch available. (MMPSC 130/30).
- Cable Entry: Standard = Right hand entry (shown above). Also available Left hand entry.
- Custom cable lengths, strip lengths, cable types, terminations.
- If you do not see what you need, just ask, as there is a strong possibility we can do it !

**Did you know we also sell?**



Rev. No.	Revision Note	Date	Signature
2	Datasheet Redesign	17-05-06	NG

**FORM AE043 ISS.2** As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

