





RECOMMENDED P.C.B. LAYOUT





CIRCUIT: DPDT
CONTACT CONFIGURATION

SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
<DN>	DEF	<DN>
2-3-5-6	DPEN	2-1-5-4

NOTES:
(>) = MOMENTARY

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 5A @120VAC OR 28VDC:
2A @250VAC.
5. FIXED TERM. & MOVING CONTACT:
Copper Alloy W/SILVER plate.
6. ELECTRICAL LIFE: 50,000 make-and-break cycles
at full load.
7. INSULATION RESISTANCE: 1,000M ohm min.
8. DIELECTRIC STRENGTH: 1,000V RMS @sea level.
9. OPERATING TEMP.: -30°C to +85°C.



8. DIELECTRIC STRENGTH: 1,000V RMS @sea level. 9. OPERATING TEMP.: -30°C to +85°C.										E-SWITCH® TITLE 100 DP-4 T1 B1 M6 Q E				
B	12004	REVISED PART DESCRIPTION	3/20/02	CJB										
A	11855	RELEASED FOR PRODUCTION	3/6/02	CJB										
REV.	ECN No.	DESCRIPTION	DATE	CHKD										
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED														
SCALE					2:1	DATE	3/6/02	DR	CJB	DWG	T124008	REV	B	