




CIRCUIT: DPDT

SWITCH FUNCTION			
PDS. 1	PDS. 2	PDS. 3	
<DN>	OFF	<DN>	
2-3,5-6	OPEN	2-1,5-4	

MOMENTARY=<DN>



VIEW A-A



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 5A @120VAC OR 28VDC;
2A @250VAC
- ▲ 5. FIXED TERM. & MOVING CONTACT:
Copper Alloy w/Silver Plate.
Electrical Life: 50,000 make-and-break
cycles at full load.
7. INSULATION RESISTANCE: 1,000M ohm min.
8. DIELECTRIC STRENGTH: 1000V RMS @sea level
9. OPERATING TEMP.: -30°C to 85°C
10. 2002/95/EC (ROHS) COMPLIANT

F	15518	EDIT SWITCH FUNCTION	11/15/05	PH
E	15506	CHANGED DIM FROM 7.98	11/8/05	PH
D	15499	EDIT SWITCH FUNCTION	11/4/05	PH
C	15474	CHANGED NOTE 10	10/28/05	PH
B	11596	REVISED	8/3/01	CJB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

THE INFORMATION CONTAINED IN THIS DOCUMENT
IS PROPRIETARY TO E-SWITCH AND IS
NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®				
100 DP-4 T6 B11 M1 Q E				
SCALE	DATE	DR	DWG	REV
2:1	5/11/01	CJB	T102310	F