






SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
ON	NONE	ON
2-3	OPEN	2-1



- NOTE:
- 1. ALL DIMENSIONS IN MM [INCH]
 - 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 - 3. TERMINAL NUMBERS FOR REF ONLY
 - ▲4. PLATING MATERIAL: GOLD
 - 5. RATING: 0.4 (VA) MAX. @20V MAX.
 - 6. ELECTRIC LIFE: 40,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
 - 7. INSULATION RESISTANCE: 1,000 MEGA-OHM MIN.
 - 8. DIELECTRIC STRENGTH: 1,000 V RMS @SEA LEVEL.
 - 9. OPERATING TEMP.: -30°C to 85°C
 - 10. ▲DENOTES CRITICAL PARAMETER.



ISOMETRIC

E-SWITCH®

A	14724	RELEASED FOR PRODUCTION	2/25/05	AR
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

TITLE 100SP1T7B13M1RE				
SCALE 2:1	DATE 2/25/05	DR AR	DWG T111111	REV A