






RECOMMENDED PANEL MOUNTING

*BOTTOM VIEW
BRACKET CLIPPED
FOR CLARITY*

PANEL THICKNESS


* DIMENSION IS 15.75/15.88
FOR PANEL THICKNESS BETWEEN
1.52mm (0.060") AND 1.68mm (0.066")

SWITCH FUNCTION		
PDS. 1	PDS. 2	PDS. 3
ON	OFF	ON
2-3,5-6	OPEN	2-1,5-4

CIRCUIT: DPDT

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 5A@ 120V AC or 28V DC;
2A@ 250V AC
5. MATERIAL: FIXED TERMINAL & MOVING CONTACT:
Copper Alloy w/Silver Plating
6. CONTACT RESISTANCE: 10mILLI Ohms max initial
@2-4VDC, 100mA for AG & AU
7. ELECTRICAL LIFE: 50,000 make-and-break
cycles at full load.
8. INSULATION RESISTANCE: 1,000M ohm min.
9. DIELECTRIC STRENGTH: 1000V RMS @sea level
10. OPERATING TEMP.: -30°C to 85°C

**E-SWITCH®**

TITLE

300 DP-3 R1 BLK M1 Q E

SCALE

2:1

DATE

6/5/02

DR

CB

DWG

T323999

REV

A

THE INFORMATION CONTAINED IN THIS DOCUMENT
IS PROPRIETARY TO E-SWITCH AND IS
NOT TO BE COPIED OR TRANSFERRED

A	12205	RELEASED FOR PRODUCTION	6/5/02	CB
REV.	ECN No.	DESCRIPTION	DATE	CHKD