


SHEET 1 OF 1






YELLOW LED

PARAMETERS	SYMBOL	MAX. / MIN.	TYP.	UNITS
POWER DISSIPATION	P_D	100 / --		mW
AVE FORWARD CURRENT	I_{AF}	30 / --		mA
PEAK FORWARD CURRENT	I_{PF}	80 / --		mA
FORWARD VOLTAGE	V_F	2.8 / 1.8	2.1	V
REVERSE VOLTAGE	V_R	5 / --		V
REVERSE CURRENT	I_R	100 / --		μA
EMISSION WAVELENGTH	λ_P		590	nm
LUMINOUS INTENSITY	I_F	/ 5.0	12.2	mcd







YELLOW LED


PARAMETERS	SYMBOL	MAX. / MIN.	TYP.	UNITS
POWER DISSIPATION	P_D	100 / --		mW
AVE FORWARD CURRENT	I_{AF}	30 / --		mA
PEAK FORWARD CURRENT	I_{PF}	80 / --		mA
FORWARD VOLTAGE	V_F	2.8 / 1.8	2.1	V
REVERSE VOLTAGE	V_R	5 / --		V
REVERSE CURRENT	I_R	100 / --		μA
EMISSION WAVELENGTH	λ_P		590	nm
LUMINOUS INTENSITY	I_F	/ 5.0	12.0	mcd

NOTE:
1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
   X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. RATINGS: 12mA @ 12VDC
5. CONTACTS: FIXED AND MOVING:
   COPPER ALLOY W/GOLD PLATE
6. OPERATING FORCE: 170 +/- 50 grams
7. OPERATING TRAVEL: 2.5MM ± 0.5MM
8. ▲ DENOTES CRITICAL PARAMETER.
9. OPERATING LIFE: 500,000 CYCLES MIN.
10. CONTACT RESISTANCE: 50OHMS MAX (INITIAL)
11. INSULATING RESISTANCE: 100M OHM MIN
12. OPERATING TEMP.: -10°C TO 60°C





CIRCUIT: SPDT



E-SWITCH®

REV	PCR NO	DESCRIPTION	DATE	BY
B	21691	CONVERTED TO INVENTOR	10/27/14	AS

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

TITLE 5501M133

SCALE	DATE	DR	DWG	REV
1:1	10/27/2014	AS	XR0178P	B