


RECOMMENDED PANEL CUTOUT
PANEL THICKNESS 1.0 - 11.0 [.04 - .43 in]

Ø22.00
[.866 in]






▲ FLAT
ACTUATOR FINISH:
BLACK ANODIZED



▲ SWITCH FUNCTION


POS. 1	POS. 2
ON	(ON)
1-3	1-2

(ON) = MOMENTARY



NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. CONTACT MATERIAL: SILVER
5. RATING: 2A 24VDC
6. ELECTRIC LIFE: 50,000 MAKE-AND-BREAK CYCLES AT FULL LOAD AT FULL LOAD.
7. INSULATION RESISTANCE: 1,000 MΩ MIN.
8. DIELECTRIC STRENGTH: 2,000 VAC MIN. FOR 1 MINUTE
9. CONTACT RESISTANCE: 50mΩ MAX. @ 1A 12VDC
10. OPERATING TEMP.: -40°C TO 85°C
11. TRAVEL: 2.5 [.10 in]
12. ▲ DENOTES CRITICAL PARAMETER
13. INGRESS PROTECTION: IP67
- ▲ 14. HARDWARE SUPPLIED: O-RING AND HEXNUT (NOT SHOWN)
- ▲ 15. ILLUMINATION VOLTAGE: NO LAMP



REV	ECO NO	DESCRIPTION	DATE	BY					OBJECT ID
E	ECO-104373	TERMINAL DIM TO 27.5 AND 35.0	09/23/26	MR	TITLE PV4F2B011				000002581
					SCALE	DATE	DR	DWG	REV
					1:1	10/3/2011	BGL	52-PV4F2B011	E

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED