




RECOMMENDED PANEL MOUNTING

PANEL THICKNESS	X
0.75-1.25	19.20-19.30
1.25-2.00	19.30-19.40
2.00-3.00	19.50-19.60




PC MOUNTING

▲ HOUSING
COLOR: BLACK▲ ACTUATOR
COLOR: RED
with
WHITE GRAPHIC




SWITCH FUNCTION		
POS. 1 (ON)	POS. 2 OFF	POS. 3 (ON)
1-1a	NONE	1-1b

(ON) = MOMENTARY

CIRCUIT: SPDT
(ON)-OFF-(ON)

NOTES:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
- TERM. NOS. FOR REF. ONLY
- RATING: 15A @125VAC [cURus]
10A @250VAC [cURus]
6A @250VAC [VDE]
- ▲ 5. LAMP VOLTAGE: NO LAMP
- MATERIAL:
CONTACT SURFACE: SILVER ALLOY
TERMINAL: COPPER ALLOY w/SILVER PLATE
- ELECTRICAL LIFE: 10,000 CYCLES
- CONTACT RESISTANCE: <20 MILLI-OHMS INITIAL
- DIELECTRIC STRENGTH: >1,500V AC 1 MIN
- ▲ DENOTES CRITICAL PARAMETER.



REV	ECO NO	DESCRIPTION	DATE	BY
B	ECO-104229	Print update	07/08/26	MW



E-SWITCH®

OBJECT ID
000016601TITLE
R1966IBLKREDHRSCALE
3:2DATE
7/2/2018DR
MWDWG
M301273REV
BTHE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO
E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED