


SHEET OF




INCANDESCENT BULB


PARAMETERS	SYMBOL	MAX.	UNITS
LAMP VOLTAGE (AC/DC)	V	24	V
POWER DISSIPATION	P_D	2	Watts
CURRENT	I	50	mA








PANEL THICKNESS	X dimension
0.75–1.25 [.030–.049]	19.2 -0.1 [.756]
1.25–2.0 [.049–.079]	19.4 -0.1 [.764]
2.0–3.0 [.079–.118]	19.8 -0.1 [.780]



CIRCUIT: DPST



PANEL CUTOUT
NOT TO SCALE

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
   X.XX=±0.25
3. RATING:
   6A @250VAC;9A @125VAC (UL, CSA, VDE)
   4(1)A @250VAC
4. LAMP VOLTAGE: 24VDC (INCANDESCENT BULB)
5. MATERIAL:
   CONTACT SURFACE: Coin Silver, Silver Plate
   TERMINAL: Copper Alloy W/ Silver Plate.
6. CONTACT RESISTANCE: 20mILLIOHMS TYP. INITIAL
7. INSULATION RESISTANCE: 1000MegaOHMS
8. DIELECTRIC STRENGTH: >1500V RMS min. @SEA LEVEL
   >3000V RMS @SEA LEVEL
9. MECHANICAL LIFE: 50,000 CYCLES.
10. ELECTRICAL LIFE: 10,000 CYCLES.

OBSOLETE
July 2020
PCR 24420

REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	11330	RELEASED FOR PRODUCTION	10/02/01	CJB

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®

TITLE: R1973B BLK YEL EF4

SCALE	DATE	DR	DWG	REV
1.5:1	10/02/01	CJB	M400043	A