



DIMENSIONS:	
A	1.688" ± 0.031
B	1.250" ± 0.031
C	1.450" ± 0.063
D	0.018" X 0.041" ± 0.005
E	1.100" ± 0.031
F	0.125" X 0.030" ± 0.005
G	0.250" ± 0.031
H	1.670" ± 0.031
J	0.460" ± 0.031



ELECTRICAL DATA:			
TESTS	CONDITIONS	ACCEPTANCE CRITERIA	
lex	@ 115V, 60Hz, PIN 1 - PIN 2	26.4mA	Max.
Sec. N.L.V	@ 115V, 60Hz, PIN 1 - PIN 2		
	PIN 3 - PIN 4 =	115.0V	$\pm 2\%$
	PIN 5 - PIN 6 =	15.05V	$\pm 2\%$
	PIN 7 - PIN 8 =	15.05V	$\pm 2\%$
DCR	@ 20°C, PIN 1 - PIN 2 =	361.6 Ω	$\pm 20\%$
	@ 20°C, PIN 3 - PIN 4 =	443.6 Ω	$\pm 20\%$
	@ 20°C, PIN 5 - PIN 6 =	6.753 Ω	$\pm 20\%$
	@ 20°C, PIN 7 - PIN 8 =	6.753 Ω	$\pm 20\%$
HIPOT	PRIMARY - SECONDARY	2000V, 60Hz, 1 SEC	

REV.#	REVISION	DATE	ELECTRONIC DIVISION			
0	RELEASED.	06/08/22	52 RANKIN PLACE,			
			WATERLOO, ONTARIO, N2J 3Z5			
			PH # (519) 886-6181			
			FAX # (519) 886-9540			
			DWG. BY: C. ILIE	CHK'D BY:	TITLE: PC BOARD MOUNT POWER TRANSFORMER	
			DATE: 06/08/22	APP'D. BY:		
				DIMENSIONS: IN(X) MM()	DWG. NO. 160F24	

