



DIMENSIONS:	
A	0.250" ±0.030
B	0.250" ±0.030
C	1.220" ±0.030
D	0.041" x 0.018" ±0.005
E	0.735" ±0.030
F	0.040" ±0.005
G	0.234" ±0.005

DIMENSIONS:	
H	1.170" ±0.030
J	0.290" ±0.030
K	0.530" ±0.030
L	1.375" ±0.030
M	0.350" ±0.030
N	0.970" ±0.030
W	1.125" ±0.030

PRIMARY SECONDARY



PIN #'S EMBOSSED
ON BOBBIN FLANGE

ELECTRICAL DATA:

TESTS	CONDITIONS	ACCEPTANCE CRITERIA	
lex	@ 115V, 60Hz, PIN 1 - PIN 2	26.4mA	Max.
Sec. N.L.V	@ 115V, 60Hz, PIN 1 - PIN 2		
	PIN 3 - PIN 4 =	115.0V	±2%
	PIN 5 - PIN 6 =	7.713V	±2%
	PIN 7 - PIN 8 =	7.713V	±2%
DCR	@ 20°C, PIN 1 - PIN 2 =	572.8 Ω	±20%
	@ 20°C, PIN 3 - PIN 4 =	572.8 Ω	±20%
	@ 20°C, PIN 5 - PIN 6 =	2.463 Ω	±20%
	@ 20°C, PIN 7 - PIN 8 =	2.463 Ω	±20%
HIPOT	PRIMARY - SECONDARY	2500V, 60Hz, 1 SEC	

REV.#	REVISION	DATE	HAMMOND MANUFACTURING™ ELECTRONIC DIVISION			
0	RELEASED.	C.I. 04/16/21	52 RANKIN PLACE,			
1	ADDED MORE DIMENSIONS.	C.I. 03/19/24	WATERLOO, ONTARIO, N2J 3Z5			
			DWG. BY: C. ILIE	CHK'D BY:	TITLE: PC BOARD MOUNT	DWG. NO.
			DATE: 04/16/21	APP'D. BY:	POWER TRANSFORMER	162E12
				DIMENSIONS: IN(X) MM()		

PH # (519) 886-6181
FAX # (519) 886-9540