

## In-Wall Timer - 24-Hour Heavy-Duty Mechanical In-Wall Timer, 125VAC, 15 A, Permanent Trippers, White

Item E1010



### PRODUCT DESCRIPTION

These Heavy-Duty In-Wall Timers are ideal for turning on lights, fans, pumps and other heavy duty loads for energy savings, security and convenience. The timer provides up to 12 ON and 12 OFF operations per day.

### FEATURES

- ▶ E1010 includes one ON/OFF permanently attached tripper for single ON/OFF control per 24-hour period
- ▶ E1020 includes two ON/OFF trippers and can accommodate up to 12 ON/OFF trippers
- ▶ Programmable in 30-minute intervals
- ▶ Turns ON/OFF heavy-duty loads for energy savings, security and convenience
- ▶ Mounts to any standard junction box
- ▶ Requires neutral connection

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

### TECHNICAL DATA

General	
Model Number	E1010
Description	24-Hour Heavy-Duty Mechanical In-Wall Timer, 125VAC, 15 A, Permanent Trippers, White
UPC Code	078275440005
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Application Compatibilities	Incandescent; Fluorescent; CFL
Harmonized Code	9107.00.8000
Control Specifications	
Minimum ON/OFF Times	30 min
Maximum ON/OFF Operations	1
Operation Mode	24-hour
Mechanism Type	Analog/Mechanical
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.25 x 3.25 x 1.375 in
Material Specifications	
Color	White
Includes Wall Plate	Yes
Load Ratings	

Resistive Load Ratings Ranges	15 A, 125 VAC, 60 Hz
Motor Load Ratings Ranges	12 FLA @ 125 VAC, 60 Hz
Incandescent Load Ratings (Single-Gang)	1500 W, 125 VAC, 60 Hz
Incandescent Single Gang Load Ratings Ranges	1500 W, 125 VAC, 60 Hz

### Electrical Specifications

Input Voltage Range(s)	125 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes

### Environmental Specifications

Temperature (operation)	-4 - 77 °F / -20 - 25 °C
-------------------------	--------------------------

### Packaging

Shipping Weight (lbs)	0.748
Unit Carton Dimensions (H x W x D) in	3.251 x 3.501 x 5.501 in

### Standards and Certifications

CSA Certification	cCSAus
California Proposition 65	DEHP
PDF Standards And Certifications	cCSAus
Epi Certifications	cCSAus

---

## ACCESSORIES



156EB1945A  
Trippers for E1020 (Pack of 2)