

## Occupancy Sensor - Residential In-Wall Push Button PIR Occupancy Sensor, White

Item IOS-DPBIF-WH



### PRODUCT DESCRIPTION

The passive infrared sensors work by detecting the difference between heat emitted from the human body in motion and the background space. The sensor switch can turn a load ON and hold it as long as the sensor detects occupancy. After no motion is detected for the set time delay, the load turns OFF automatically. The sensor switch has one relay (equal to single pole switch), it also includes Ambient Light Level Sensor.

### FEATURES

- ▶ Passive Infrared (PIR) sensing for presence detection
- ▶ Adjustable PIR sensitivity
- ▶ Adjustable time delay 15 sec to 30 min
- ▶ Adjustable ambient light sensor override for occupancy switch models
- ▶ Coverage: 150°, 980 ft<sup>2</sup> with non-obstructed views
- ▶ IOS-DPBIF and IOS-DPBV models are Incandescent/Fluorescent/CFL/LED compatible and require a neutral connection
- ▶ 'No neutral' models offered for retrofit applications
- ▶ Fits standard decorator wall plate (included)
- ▶ Occupancy (Automatic ON/ Manual or Automatic OFF)
- ▶ For use with Magnetic Ballasts
- ▶ Adjustable Ambient Light level detection

### APPLICATIONS

- ▶ Indoor Sensing Control

### TECHNICAL DATA

#### General

Model Number	IOS-DPBIF-WH
Description	Residential In-Wall Push Button PIR Occupancy Sensor, White
UPC Code	078275125254
Brand	Intermatic
Warranty Period	2-Year limited
Country of Origin (Intermatic)	CHINA
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Market	Commercial; Industrial; Residential; Utility

#### Control Specifications

Sensor Switch Type	Occupancy
Sensor Technology	PIR (Passive Infrared)
Adjustable Time Delay Min	15 sec
Adjustable Time Delay Max	30 min
Adjustable Light Level Min	30 lux
Adjustable Light Level Max	Daylight
PIR Coverage Area (sq ft)	980

#### Mechanical Specifications

Mount Type	In-Wall
PIR Coverage Pattern (degrees)	150
Maximum Mounting Height (ft)	4 ft

Dimensions	
Product Height (in)	2.75
Product Height (mm)	70
Product Width (in)	1 7/16
Product Width (mm)	37
Product Depth (in)	1.625
Product Depth (mm)	41

Material Specifications	
Color	White
Includes Wall Plate	Yes

Load Ratings	
Resistive Heater	12 A
Inductive Load Ratings Ranges	800 VA
Motor Load Ratings Ranges	1/4 HP
Ballast Fluorescent Ranges	800 VA
Tungsten (Incandescent) Range(s)	800 W

Electrical Specifications	
Input Voltage Range(s)	120 VAC, 60 Hz
Occupancy Sensor Power Type	Line Voltage
Neutral Connection Required	Yes

Packaging	
Shipping Weight (lbs)	0.4
Shipping Weight (kg)	0.181
Unit Carton Dimensions (H x W x L) in	5 x 2.25 x 3 in

Environmental Specifications	
Temperature (operation)	32 - 131°F / 0 - 55°C

Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	Title 20
California Proposition 65	None
Epi Certifications	Title 20; cULus