

In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 15,30,45 Minute,1,2 Hour, Without Hold, White

Item EI235W





PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- No programming required
- ▶ Provides silent operation in time ranges from 15 minutes to 2 hours
- ► Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ► Replaces single-pole switches in a variety of applications
- ► Incandescent/fluorescent/CFL/LED compatible
- ► For use with decorator-style wall plate (not included)
- ► Requires neutral connection

APPLICATIONS

- ► Indoor Lighting Control
- ► Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	El235W
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 15,30,45 Minute,1,2 Hour, Without Hold, White
UPC Code	078275111202
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Harmonized Code	9107.00.4080

Control Specifications	Specifications	
Time Presets	15 min; 30 min; 45 min; 1 hr; 2 hrs	
Setpoint Program Count	5	
Operation Mode	Countdown	
Countdown Time	2 hrs	
Hold Mode Included	No	
Mechanism Type	Digital/Electrical	

Mechanical Specifications		
Wall Plate Configurations	Single-Gang	
Dimensions		

4.125 x 1.688 x 1.438 in

Product Dimensions (H x W x D) in

Material Specifications



Color White

Load Ratings	l Ratings	
Resistive Heater	15 A, 1800 W	
Tungsten (Incandescent) Range(s)	1000 W	
Ballast Fluorescent	8 A, 1000 VA	
Electronic Ballast LED	4 A, 500 VA	
Motor Load Ratings Ranges	1/4 HP	

Electrical Specifications		
Input Voltage Range(s)	120 VAC, 60 Hz	
Wiring Configurations	Single	
Neutral Connection Required	Yes	

Environmental Specifications	mental Specifications	
Temperature (operation)	32 - 104 °F / 0 - 40 °C	

ckaging	
Shipping Weight (lbs)	0.4
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

ndards and Certifications	
UL Certification	cULus
California Proposition 65	DEHP
RoHS Certification	Yes
PDF Standards And Certifications	cULus
Epi Certifications	cULus