

In-Wall Timer - 7-Day Standard Programmable Timer, 125 VAC, 15A, Ivory

Item EI500C



PRODUCT DESCRIPTION

For installation on 15 A circuits, this timer provides 24-hour or 7-day programming of lights, fans, pumps and other medium-duty loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ 7-day programmable schedules with 14 ON/OFF events
- ▶ Automatic Daylight Saving Time (DST) adjustment
- ▶ Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- ▶ Single-pole circuit
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ Built-in rechargeable, non-serviceable battery backup
- ▶ Requires neutral connection
- ▶ Backlit LCD display
- ▶ Decorator switch plate not included

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	EI500C
Description	7-Day Standard Programmable Timer, 125 VAC, 15A, Ivory
UPC Code	078275105218
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Harmonized Code	9107.00.8000
Control Specifications	
Minimum ON/OFF Times	1 min
Maximum ON/OFF Operations	14
Operation Mode	24-hour
Mechanism Type	Digital/Electrical
Backup Type	Battery
Battery Type	Rechargeable
Battery Service Type	Non-Serviceable
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.4375 in

Material Specifications

Color	Ivory
Includes Wall Plate	Yes

Load Ratings

General Purpose	15 A, 125 VAC, 60 Hz
Resistive Heater	15 A, 1875 W
Tungsten (Incandescent) Range(s)	1000 W
Ballast Fluorescent	8 A, 1000 VA
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP, 125 VAC, 60 Hz
Inductive Load Ratings Ranges	1000 VA, 125 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s)	125 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes

Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.351
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

Standards and Certifications

UL Certification	cULus
California Proposition 65	DEHP
PDF Standards And Certifications	cULus
Epi Certifications	cULus