

In-Wall Timer - Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 12 Hour Max, With Hold, Ivory

Item FD12HH



PRODUCT DESCRIPTION

The FD Series Decorator Countdown Timers are designed to replace any standard or decorator style wall switch, single- or multigang. These mechanical timers do not require electricity to operate. They automatically limit the ON times for fans, lighting, motors, heaters and other energy consuming loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ► 12-Hour timer with hold
- SPST (Single-Pole Single-Throw)
- No electricity required to operate
- Replaces any standard or decorator single- or multi-gang wall switch
- ► Automatically limits ON time for energy consuming loads
- Quick and easy installation
- Time-saving up front terminal connection with teeter-type terminals
- Breaks circuit at end of timing cycle
- ► Incandescent/fluorescent/CFL/LED compatible
- No neutral connection is required
- Decorator switch plate not included
- ► Operates in temperatures down to -40° C

APPLICATIONS

- ► Indoor Lighting Control
- Outdoor Lighting Control
- Motor Control
- ► Air Movement & Ventilation

TECHNICAL DATA

FD12HH
Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 12 Hour Max, With Hold, Ivory
078275185708
Intermatic
TUNISIA
1-Year limited
Incandescent; Fluorescent; CFL; LED
9107.00.8000
Countdown
12 hrs
Yes
Analog/Mechanical
Single-Gang; Multi-Gang



Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.25 in
	4.120 X 1.70 X 1.20 III
Material Specifications	
Color	lvory
Load Ratings	
Resistive Heater	20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC
Tungsten (Incandescent) Range(s)	7 A, 125 VAC, 50/60 Hz, 875 W
Motor Load Ratings Ranges	1 HP, 125 VAC; 2 HP, 250 VAC
Electrical Specifications	
Input Voltage Range(s)	125-277 VAC, 50/60 Hz
Wiring Configurations	Single
Switch Type	SPST
Neutral Connection Required	No
Environmental Specifications	
Temperature (operation)	40 - 120 °F / 4 - 49 °C
Packaging	
Shipping Weight (lbs)	0.299
Unit Carton Dimensions (H x W x D) in	4.63 x 2.13 x 2.88 in
Standards and Certifications	
CSA Certification	cCSAus
Other Certifications and Compatibilities	RU
California Proposition 65	DEHP



ACCESSORIES



146MT573 Knob-Wall Switch FD Series - Ivory



146MT574 Knob-Wall Switch FD Series - White



Knob-Wall Switch FD Series - Almond



148FD5074 Plate for 12-Hr with HOLD, Ivory (FD12HH)