




KYCON, Inc. 305 Digital Drive, Morgan Hill, CA 95037 (408)494-0330

















LED Specification

LED Color	LED Wavelength	Forward(A)	Forward(V)
Green	565nm	20mA	2.2~2.4V
Yellow	590nm	20mA	2.1~2.5V

Materials and Finish

Housing Material:
High Temperature Thermoplastic, UL 94V-0 Rated, Color: Black

Shield: Brass, Nickel Plated

Contact Material:
Phosphor Bronze

Contact Plating:
Nickel Underplating, W/ 30u" Gold Plating on Contact Area,

Electrical Characteristics

Dielectric Withstanding Voltage:
2250V DC for 60 Seconds
Primary to Secondary

Mechanical Characteristics

Mating Force: 23N Max.

Durability Rating:
750 Mating Cycles Min.

Operating Temperature:
-40°C to +85°C

Electrical Properties Of Magnetics

Insertion Loss (dB Max)		Return Loss (dB Min)			Cross Talk (dB Min)		CMR (dB Min)			CDMR (dB Min)		OCL (uH Min)
100 KHz	1~400 MHz	1~40 MHz	40~400 MHz	400~500 MHz	1~100 MHz	100~500 MHz	1~40 MHz	40-100 MHz	100~500 MHz	1-250 MHz	250~500 MHz	@100 KHz & 100 mV, 8 mA
-3.0	-2.0	-16	-16+10Log(f/40)	-6+30Log(f/400)	-28	-19	-30	-28	-26	-30	-22	160

RoHS COMPLIANT

Tolerances
X.X ± 0.30
X.XX ± 0.25
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY
A0	07/11/24	New Drawing	C. Kelleher	C. Kelleher
A1	11/25/24	Release Drawing	C. Kelleher	N/A
A2	03/26/25	ECO #25-027	K.Wang	C. Kelleher

DRAWN BY	DATE
C. Kelleher	06/28/24
	UNITS
	mm

G13LX-188S7-10G-YG/G-30

Modular Jack, w/10G Magnetics, Fully Shielded,

Top & Side Tabs, Yel/Grn & Grn LEDs, RoHS

KYCON