

## MODULAR JACKS AND PLUGS: GDLX Series

### Right Angle Modular Jack

#### Product Features

Available in high temp for Reflow compatibility  
 Panel Stops, Shielding and Keying Options Available  
 Snap-In Board Retention Tabs  
 CSA/NRTL Certified File No. LR78160

#### Performance Specifications

##### Materials and Finish

###### Housing Material

PBT Thermoplastic, Glass Filled, UL 94V-0 Rated,  
 Black Color

###### Shield Material

Copper Alloy, Nickel Plated

###### Contact Material

Phosphor Bronze

#### Electrical Characteristics

##### Insulation Resistance

500 Megohms Min.

##### Dielectric Withstanding Voltage

1000V AC for 1 Minute

##### Contact Resistance

20 milliohms Max.

##### Current Rating

1.5A


##### Voltage Rating

125V DC

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

#### Part Number Builder



#### Series

GDLX - Right Angle Modular Jack PCB Mount

#### Shield Options

- A - With Panel Stops, Non-Shielded
- N - Without Panel Stops, Non-Shielded
- S - With Panel Stops, Shielded

#### Number of Positions / Contacts

- 64 - 6 Positions / 4 Contacts
- 66 - 6 Positions / 6 Contacts
- 88 - 8 Positions / 8 Contacts

#### Plating Option

- Blank - Gold Flash
- 50 - 50µ" Gold Plating

Contact Kycon for Keyed and other Options

#### GDLX Series

Dimensions in mm

##### GDLX-A-64

