


KYCON, Inc. 305 Digital Drive, Morgan Hill, CA 95037 (408)494-0330







Recommended PCB Layout
(Top View)

Materials and Finish

Housing Material-
PBT thermoplastic
UL 94V-0 rated

Contact Material-
phosphor bronze

Contact Plating Options-
Standard: gold flash on contact area, tin on solder area, all over nickel underplate

15: 15u" gold on contact area, tin on solder area all over nickel underplate

50: 50u" gold on contact area, tin on solder area all over nickel underplate

Electrical Characteristics

Current Rating:
1.5 Amps

Voltage Rating:
125V DC

Insulation Resistance:
500 Megohms min.

Dielectric Withstanding Voltage:
1000V rms, 60Hz

Contact Resistance:
20 milliohms max.

Operating Temperature:
-40°C to +85°C

Part Number	Contact Area Plating Finish	Color
GLX-N-44	Gold Flash (standard)	Grey
GLX-N-44-15	15u" Gold (15 option)	Grey
GLX-N-44-50	50u" Gold (50 option)	Grey
GLX-N-44-BLK	Gold Flash (standard)	Black

RoHS COMPLIANT

E134345 LR78160

Tolerances
X.X ± 0.35
X.XX ± 0.25
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY
A2	05/13/10	ECO #10-025	S. Vien	H. MA
A3	12/07/11	ECO #11-081	S. Vien	H. MA
A4	12/12/13	ECO #13-091	D. Gih	H. MA
A5	06/01/17	Updated Address	H. MA	N/A
A6	10/24/25	ECO #25-048	K.Wang	C.Kelleher
A7	04/10/26	ECO #26-006	C. Kelleher	K. Wang

DRAWN BY	DATE
R. Aguirre	9/16/05
	UNITS
	mm

GLX-N-44

PCB Mount, Modular Jack, Rt Ang.

4 Postion, 4 Contact, RoHS Compliant

KYCON