



UNIVERSAL SERIAL BUS: KUSBVX-SMT Series

USB Type C Socket, 3.2 GEN2 Receptacle, High Retention Short Shield Pins, Vertical,SMT,T/R, CAP

Product Features

USB Version 3.1
Gen 2 (10 Gbps)
Vertical Mount
SMT Contacts

Performance Specifications

Materials and Finish

Housing

High Temperature Thermoplastic, UL94V-0 Rated

Shell:

Stainless Steel, Nickel Plated

Contact Material

Copper Alloy

Contact plating

30µ" Gold Plated on Contact Area.

Matte Tin Plated on Solder Tails,

All over Nickel Underplate

Electrical Characteristics

Rated Current

5.0A

Rated Voltage: 30V

Insulation Resistance

100 Megohms Min. at 250V DC

Contact Resistance

40 milliohms Max.

Dielectric Withstanding Voltage

100V AC RMS For 1 Minute

Mechanical Characteristics

Insertion Force: 0.5N - 2.0 Kgf

Withdrawal Force: 1.5 Kgf MIN

Durability: 10000 Mating Cycles Min.

Operating Temperature:

-55°C to +85°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

KUSBVX-SMT-CS-O30HRFTRC

Part Number Builder

KUSBVX-SMT

Series

CS

Type

O

Insulator
Color

30

Plating

HRF

Option

TRC

Packaging

Series

KUSBVX-SMT - USB Type C Socket, 3.2 GEN2 Receptacle, High Retention Short Shield Pins, Vertical,SMT,T/R, CAP

Type

CS - C Type

Insulator Color Option

O - Orange

Plating Option

30 - 30µ"Gold Plating

Option

HRF - High Retention Force

Packaging

TRC - Tape and Reel with Cap

Contact Kycon for more options

KUSBVX-SMT

Dimensions in mm

