# Product data sheet

Specifications



## connection cable - Twido discrete output to Telefast - 2 x HE10 - 3 m

ABFTE20SP300

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | Twido |
| **Accessory / separate part designation** | Discrete output pre-formed cable |
| **Accessory / Separate Part Type** | Connecting cable |
| **Accessory / separate part category** | Connection accessories |
| **Accessory / separate part destination** | Discrete output |
| **Product Specific Application** | For application other than use of Advantys Telefast ABE7 sub-base |

## Complementary

| | |
|---|---|
| **Product Compatibility** | TWDDDO16TK<br>TWDDDO32TK |
| **Cable length** | 9.8 ft (3 m) |
| **AWG Gauge** | 28 AWG |
| **Cable cross section** | 0.0001 in² (0.08 mm²) |
| **Electrical connection** | 1 connector HE10 20 preactuator side<br>1 connector HE10 20 Twido side |
| **Net Weight** | 0.46 lb(US) (0.21 kg) |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CP222375 |
| **Discount Schedule** | 0CP2 |
| **GTIN** | 3389110393774 |
| **Returnability** | No |
| **Country of origin** | TH |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 1.535 in (3.900 cm) |
| **Package 1 Width** | 7.244 in (18.400 cm) |
| **Package 1 Length** | 7.874 in (20.000 cm) |
| **Package weight(Lbs)** | 6.808 oz (193.000 g) |
| **Unit Type of Package 2** | S02 |
| **Number of Units in Package 2** | 10 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Package 2 Height** | 5.906 in (15.000 cm) |
| **Package 2 Width** | 11.811 in (30.000 cm) |
| **Package 2 Length** | 15.748 in (40.000 cm) |
| **Package 2 Weight** | 4.899 lb(US) (2.222 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Use Better

#### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **Yes** |
| Packaging without single use plastic | **No** |
| EU RoHS Directive | **Compliant** |
| REACh Regulation | **Free of Substances of Very High Concern above the threshold** |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov** |

### Use Again

#### Repack and remanufacture

| | |
|---|---|
| Take-back | **No** |
| WEEE Label | **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.** |