Product data sheet

Specifications



3-phase control relay, Harmony Control Relays, 8A, 2CO, undervoltage detection, 380...480V AC

RM22TU23

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony Control Relays
Relay Type	Control relay
Product or Component Type	3-phase control relay
Relay name	RM22TR
Relay monitored parameters	Undervoltage detection Phase sequence Phase failure detection
Control Type	With test button
Contacts type and composition	2 C/O

Complementary

[Us] rated supply voltage	, self-powered
Supply voltage limits	304…576 V AC
Supply frequency	50...60 Hz +/- 10 %
Power consumption in VA	15 VA 480 V AC 60 Hz
Measurement range	380...480 V voltage AC
Voltage detection threshold	< 100 V AC
Maximum measuring cycle	150 ms measurement cycle as true rms value
Threshold adjustment voltage	2...20 % of Un selected
Setting accuracy of the switching threshold	+/- 10 % of the full scale
Repeat accuracy	+/- 0.5 % input and measurement circuit
Measurement error	< 1 % over the whole range with voltage variation < 0.05 %/°C with temperature variation
Time delay type	Without
Setting accuracy of time delay	10 %
Reset time	1500 ms at maximum voltage
Response time	<= 300 ms
Output contacts	2 C/O
nominal output current	8 A
Maximum switching voltage	250 V AC
Switching capacity in VA	2000 VA
Minimum switching current	10 mA 5 V DC

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum switching current	8 A AC
Electrical durability	100000 cycles
Mechanical durability	10000000 cycles
Contacts material	Cadmium free

Environment

Electromagnetic compatibility	Immunity for residential, commercial and light-industrial environments conforming to IEC 61000-6-1 Immunity for industrial environments conforming to IEC 61000-6-2 Emission standard for residential, commercial and light-industrial environments conforming to IEC 61000-6-3 Emission standard for industrial environments conforming to IEC 61000-6-4 Electrostatic discharge - test level: 6 kV level 3 (contact discharge) conforming to IEC 61000-4-2 Electrostatic discharge - test level: 8 kV level 3 (air discharge) conforming to IEC 61000-4-2
Standards	IEC 60255-1
Product Certifications	CSA RCM UL GL CE CCC EAC
Ambient Air Temperature for Storage	-40…158 °F (-40…70 °C) -40…158 °F (-40…70 °C)
Ambient air temperature for operation	-4…122 °F (-20…50 °C) 60 Hz -4…140 °F (-20…60 °C) 50 Hz AC/DC
Relative humidity	93…97 % 77…131 °F (25…55 °C) IEC 60068-2-30
Vibration resistance	0.075 mm 10…58.1 Hz) not in operation IEC 60068-2-6 1 gn 10…58.1 Hz) not in operation IEC 60068-2-6 0.035 mm 58.1…150 Hz) in operation IEC 60068-2-6 0.5 gn 58.1…150 Hz) in operation IEC 60068-2-6
Shock resistance	15 gn 11 ms) not in operation IEC 60068-2-27 5 gn 11 ms) in operation IEC 60068-2-27
IP degree of protection	IP20 IEC 60529 terminals) IP40 IEC 60529 housing) IP50 IEC 60529 front panel)
Pollution degree	3 IEC 60664-1 3 UL 508
Overvoltage category	III conforming to IEC 60664-1 III conforming to UL 508
Dielectric test voltage	2.5 kV AC 50 Hz, 1 min IEC 60255-27
Insulation resistance	> 100 MOhm 500 V DC IEC 60255-27
Connections - terminals	Screw terminals, 2 x 0.5...2 x 2.5 mm² 20 AWG...14 AWG) solid without cable end Screw terminals, 2 x 0.2...2 x 1.5 mm² 24 AWG...16 AWG) flexible with cable end Screw terminals, 1 x 0.5...1 x 3.3 mm² 20 AWG...12 AWG) solid without cable end Screw terminals, 1 x 0.2...1 x 2.5 mm² 24 AWG...14 AWG) flexible with cable end
Tightening torque	5.3…8.9 lbf.in (0.6…1 N.m) IEC 60947-1
Housing material	Polycarbonate
Local signalling	LED (Yellow) relay ON LED (Green) power ON
Mounting support	35 mm DIN rail conforming to IEC 60715
Reliability data	MTTFd = 388.1 years B10d = 350000

Height	3.5 in (90 mm) 3.5 in (88.9 mm)
Width	0.9 in (22.5 mm) 0.9 in (22.9 mm)
Depth	2.9 in (73 mm) 2.9 in (73.7 mm)
Net Weight	0.209 lb(US) (0.095 kg) 0.21 lb(US) (0.10 kg)

Ordering and shipping details

Category	US10CP222380
Discount Schedule	0CP2
GTIN	3606480792175
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.02 in (2.6 cm)
Package 1 Width	3.2 in (8.2 cm)
Package 1 Length	3.7 in (9.5 cm)
Package weight(Lbs)	3.6 oz (103.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	5.9 in (15 cm)
Package 2 Width	11.8 in (30 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	10.265 lb(US) (4.656 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	640
Package 3 Height	29.5 in (75.0 cm)
Package 3 Width	23.6 in (60.0 cm)
Package 3 Length	31.5 in (80.0 cm)
Package 3 Weight	182.975 lb(US) (82.996 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**71 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**2 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**69 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.1 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**3c095d35-159c-493c-8604-58788d456aa9**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**


Use Again

Repack and remanufacture

Recyclability potential, in %	**17**
Circularity Profile	**End of Life Information**
Take-back	**No**


Dimensions Drawings

Dimensions



Mounting and Clearance


Rail Mounting



Connections and Schema

3-Phase Undervoltage Control Relay

Wiring Diagram




L1,L2,L3 : Supply to be monitored
11-14,12 : 1st C/O contact of output relay
21-24,22 : 2nd C/O contact of output relay


Technical Description

Function Diagrams

Phase Sequence Control and Phase failure Detection



Undervoltage Control




Legend


Tr : Response time after cross the threshold
U< : Undervoltage threshold
L1, L2, L3 : Phases of the supply voltage monitored
R : Relay output 11-12/11-14, 21-22/21-24
H : Hysteresis
Relay status : black color = energized.


Image of product / Alternate images


Alternative






12
11
14
22
21
24




RM22TU23
L1
L2
L3
12
22
11
21
14
24
Use copper conductors only






Image of product in real life situation

