Product data sheet

Specifications



pre assembled relay, Harmony Solid State Relays, 2A, zero voltage switching, screw sockets, input 4 to 12V DC, output 24 to 250V AC

SSL1A12JDPV

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony Solid State Relays
Device short name	SSL
Phase	1 phase
[Uc] control circuit voltage	4...12 V
Connections - Terminals	Screw connectors
Output switching mode	Zero voltage switching

Complementary

Mounting Support	Screw socket
Line Rated Current	2 A
Output voltage	24...250 V AC
[Uc] control circuit voltage	4...12 V DC
CLAMPING FORCE	< 0.5 N.m 4.4 lb-in
Connections - terminals	Flexible cable with cable end, 0.2...2.5 mm² 24 AWG...14 AWG) Solid cable with cable end, 0.2...2.5 mm² 24 AWG...14 AWG)
Capacitance unbalance	1.5 pF input/output
Minimum switching voltage	4 V DC turn-on
Maximum switching voltage	1 V DC turn-off
Input impedance	333 kOhm
Solid state output type	Zero voltage switching SCR output
Load current	0.07…2 A
Transient Overvoltage	600 V AC
Surge current	120 A 16.6 ms 115 A 20 ms
Maximum voltage drop	<1.1 V on-state
Maximum I²t for fusing	285 A².s for 10 ms at 50 Hz 260 A².s for 8.3 ms at 60 Hz
Maximum leakage current	4 mA off-state
DV/dt	500 V/µs off-state at maximum voltage
Response time	0.5 cycle (turn-on) 0.5 cycle (turn-off)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Overvoltage category	III
Width	0.2 in (6.2 mm)
Height	3.8 in (96.5 mm)
Depth	3.1 in (79.5 mm)
Net Weight	0.0628 lb(US) (0.0285 kg)
Device presentation	Complete product

Environment

Flame retardance	V0 conforming to UL 94
Dielectric strength	2500 V for input/output
Pollution degree	2
Standards	IEC 60950-1 IEC 61000 IEC 62314 IEC 61984 EN 61984
Product Certifications	UL CSA CE UL 508 CSA22.2 No. 14-10 GOST
Marking	CURus CSA CE EAC
IP degree of protection	IP20
Ambient Air Temperature for Operation	-4…158 °F (-20…70 °C)
Ambient Air Temperature for Storage	-4…185 °F (-20…85 °C)

Ordering and shipping details

Category	US10CP221127
Discount Schedule	0CP2
GTIN	3606489562953
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.236 in (0.600 cm)
Package 1 Width	3.150 in (8.000 cm)
Package 1 Length	3.819 in (9.700 cm)
Package weight(Lbs)	0.952 oz (27.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	30
Package 2 Height	3.543 in (9.000 cm)

Package 2 Width	3.937 in (10.000 cm)
Package 2 Length	7.874 in (20.000 cm)
Package 2 Weight	31.817 oz (902.000 g)
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	11.8 in (30 cm)
Package 3 Width	11.8 in (30 cm)
Package 3 Length	15.7 in (40 cm)
Package 3 Weight	5.739 lb(US) (2.603 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**10 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**0.5 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**10 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0 kg CO2 eq.**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**


Use Again

Repack and remanufacture

Recyclability potential, in %	**27**
Take-back	**No**


Dimensions Drawings

Dimensions



Performance Curves


Derating Curves



X : Ambient Temperature (°C)
Y : Load Current (Amperes)
1 : Installed single unit, distance to adjacent components more than 6.2 mm
2 : Multiple units, no minimum spacing between components

Image of product / Alternate images


Alternative













14
NO
11/13+
COM
12
NC
Made in China
SSLXXXX
6A 250V
Supply Voltage
Control Voltage
5V
24V
Protection and Indication Circuit
A1
A2
Schneider Electric