

# Product data sheet

Specifications



## SmartX Cover Plate, for Sensor Base, Touchscreen, with 2 Button Lighting, PIR, Optimum White Cover

SXWSC2PSELXW

**Product availability:** Stock - Normally stocked in distribution facility

### Main

|                                       |                                                                                              |
|---------------------------------------|----------------------------------------------------------------------------------------------|
| Range                                 | SpaceLogic                                                                                   |
| Product or Component Type             | Cover                                                                                        |
| Product name                          | SmartX Living Space Sensor                                                                   |
| Device Application                    | HVAC Control                                                                                 |
| Product certifications                | CE conforming to EN 61000-6-3<br>RCM<br>EAC<br>ICES-003                                      |
| Display Resolution                    | 320 x 240 pixels                                                                             |
| Display size                          | 2.4 inch                                                                                     |
| Display Type                          | Colour touchscreen                                                                           |
| Information Displayed                 | Temperature<br>Temperature set point<br>Operating mode<br>Menu-driven user interface<br>Time |
| Flame Retardance                      | UL94-V0                                                                                      |
| IP Degree of Protection               | IP20                                                                                         |
| Location                              | Living Space                                                                                 |
| Depth                                 | 0.8 in (20 mm)                                                                               |
| Height                                | 4.5 in (115 mm)                                                                              |
| Width                                 | 3.3 in (85 mm)                                                                               |
| Ambient Air Temperature for Operation | 32...122 °F (0...50 °C)                                                                      |
| Standards                             | UL 916<br>FCC Part 15 class B                                                                |
| Color                                 | White                                                                                        |
| Sensor Type                           | PIR                                                                                          |
| [Us] Rated Supply Voltage             | 24 V DC                                                                                      |
| Device presentation                   | Cover plate                                                                                  |
| Surface Finish                        | Glossy                                                                                       |

### Complementary

|              |                                               |
|--------------|-----------------------------------------------|
| Control type | tactile<br>ON-OFF 2 function keys, for lamp   |
| Material     | ABS (acrylonitrile butadiene-styrene) GF10 FR |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                         |                                                                                                                                                               |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Function Available      | Override switches<br>Setpoint adjustment<br>Blind control<br>Light control                                                                                    |
| Supply                  | Base                                                                                                                                                          |
| Connections - terminals | Bus terminal back)                                                                                                                                            |
| Movement detection area | 4 m 140° 4.43 ft (1.35 m)<br>5 m of radius (wall) 110° 4.43 ft (1.35 m)<br>6 m 60° 4.43 ft (1.35 m)                                                           |
| Range compatibility     | EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers<br>EcoStruxure Building Operation SmartX Living Space Sensor base unit |

## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US1BMS180230  |
| Discount Schedule | BMS1          |
| GTIN              | 3606481732552 |
| Returnability     | Yes           |
| Country of origin | MX            |

## Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Nbr. of units in pkg.  | 1                |
| Package 1 Height       | 1.9 in (4.8 cm)  |
| Package 1 Width        | 3.8 in (9.7 cm)  |
| Package 1 Length       | 5.5 in (14.0 cm) |
| Package weight(Lbs)    | 4.3 oz (121.0 g) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                |
|--------------------------------------------------------|----------------|
| Total lifecycle Carbon footprint                       | 5 kg CO2 eq.   |
| Carbon footprint of the manufacturing phase [A1 to A3] | 3 kg CO2 eq.   |
| Carbon footprint of the distribution phase [A4]        | 0.2 kg CO2 eq. |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.   |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 1 kg CO2 eq.   |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.2 kg CO2 eq. |

## Use Better



### Materials and Substances

|                                        |                                                                                                                                                                                                                                                                          |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                                                                                                                                                                                                      |
| Packaging without single use plastic   | No                                                                                                                                                                                                                                                                       |
| SCIP Number                            | E29cd56a-1ac5-4d02-9266-937a562619e2                                                                                                                                                                                                                                     |
| EU RoHS Directive                      | <a href="#">Compliant</a>                                                                                                                                                                                                                                                |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a>                                                                                                                                                                                   |
| California proposition 65              | WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

## Use Again



### Repack and remanufacture

|                               |                                         |
|-------------------------------|-----------------------------------------|
| Recyclability potential, in % | 3                                       |
| Circularity Profile           | <a href="#">End of Life Information</a> |
| Take-back                     | No                                      |