

(!) Discontinued

General purpose relay, SE Relays, 750R, 3PDT, 10A, 24 VDC, octal terminal 11 pins, clear cover with **LED** 

750XCXRCL-24D

! Discontinued on: Aug 7, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Product Type	Plug-in electromechanical relay	
Rated Line Current	10 A	
Switch Function	3PDT	
Contact Composition	3 NO + 3 NC	

### Complementary

•		
Rated Operational Current	10 A at 277 V AC (on resistive load) conforming to UL 10 A at 30 V DC (on resistive load) conforming to UL 10 A at 250 V AC-1 (1 NO) (on resistive load) conforming to IEC 10 A at 28 V DC-1 (1 NO) (on resistive load) conforming to IEC 5 A at 250 V AC-1 (1 NC) (on resistive load) conforming to IEC 5 A at 28 V DC-1 (1 NC) (on resistive load) conforming to IEC	
[Ue] rated operational voltage	24 V DC	
Maximum Switching Voltage	300 V AC UL 30 V DC UL 250 V AC IEC 28 V DC IEC	
Mounting Support	plug-in	
Local Signalling	LED Cover Flag	
Contacts Material	Silver alloy, gold flashed	
Rated Power in HP	0.33 HP 120 V AC 1 HP 277 V AC	
Connections Terminals	octal terminal connector socket 11 pins)	
Control Circuit Voltage Limits	0.81.1 Un DC	
Resistance	470 Ohm	
Average Coil Consumption	1.4 W	
Vibration Resistance	+/- 1 mm 1035 Hz in operation 3 gn 35150 Hz in operation	
Operating Time	20 ms	
Drop-out Voltage Threshold	>= 0.15 Uc AC >= 0.1 Uc DC	
Minimum Switching Current	10 mA 17 V DC	
Product Weight	2.9 oz (83 g)	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Height	2.05 in (52 mm)	
Width	1.4 in (35 mm)	
Depth	1.4 in (35.5 mm)	

### **Environment**

Shock Resistance	10 gn	
	10 gii	
Ambient Air Temperature for Operation	-40131 °F (-4055 °C)	
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)	
<b>Product Certifications</b>	UL	
	CSA	
	CE	
	EAC	
Dielectric Strength	2500 V AC between coil and contact	
	2000 V AC between poles	
	1500 V AC between contacts	
Electrical Durability	100000 cycles	
Mechanical Durability	5000000 cycles	
IP Degree of Protection	IP40	

# Ordering and shipping details

Category	US10CP221127	
Discount Schedule	0CP2	
GTIN	3606480779459	
Returnability	No	

# **Packing Units**

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	1.40 in (3.55 cm)	
Package 1 Width	1.4 in (3.5 cm)	
Package 1 Length	1.40 in (3.55 cm)	
Package weight(Lbs)	2.9 oz (83 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	60	
Package 2 Height	5.9 in (15 cm)	
Package 2 Width	11.8 in (30 cm)	
Package 2 Length	15.7 in (40 cm)	
Package 2 Weight	14.767 lb(US) (6.698 kg)	
Unit Type of Package 3	P06	
Number of Units in Package 3	960	
Package 3 Height	41.3 in (105 cm)	
Package 3 Width	23.6 in (60 cm)	
Package 3 Length	31.5 in (80 cm)	
Package 3 Weight	254.2 lb(US) (115.3 kg)	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >


How we assess product sustainability >


#### **Use Better**

Materials and Substances		
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	

**Dimensions Drawings** 

### **Approximate Dimensions**





Connections and Schema

### **Connections and Wiring Diagrams**

