



Power Relay, Type C, DPDT, 2 normally open and 2 normally closed contacts, 20A resistive at 110 VDC, 24 VDC coil

8501CDO22V53

Product availability: Stock - Normally stocked in distribution facility

Main

product range	Power Relay 8501C	
product type	Power relay	
short name	type C	
[In] rated line current	20 A	
device application	Suited for controlling small single phase motors and other light loads	
switch function	DPDT	
contact composition	2 NO/2 NC	
[Uc] control circuit voltage	24 V DC	
maximum switching voltage	325 V DC	

Complementary

class number	8501
phase	1 phase
terminal connects	Screw clamp terminal
wire range	AWG 10 copper
terminal tightening torque	1115 lbf.in (1.21.7 N.m)
coil burden	2 W
mounting	Panel mounting

Environment

ambient temperature range - operational	-3060 °C (-22140 °F)
product certifications	UL listed file E78351 CCN NLDX CSA CE
height	3.12 in (79.25 mm)
width	2.5 in (63.5 mm)
depth	2.53 in (64.26 mm)

Ordering and shipping details

Category	US10CP221131
Discount Schedule	0CP2
GTIN	785901059615

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Returnability	Yes	
Country of origin	CN	

Packing Units

_		
Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	2.70 in (6.858 cm)	
Package 1 Width	2.90 in (7.366 cm)	
Package 1 Length	3.70 in (9.398 cm)	
Package weight(Lbs)	11.200 oz (317.514 g)	
Unit Type of Package 2	CAR	
Number of Units in Package 2	25	
Package 2 Height	4.00 in (10.160 cm)	
Package 2 Width	15.60 in (39.624 cm)	
Package 2 Length	20.70 in (52.578 cm)	
Package 2 Weight	19.899 lb(US) (9.026 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better


Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration


Dimensions



All dimensions are approximate.
Also refer to technical drawings and documentation.

Technical Illustration

Wiring diagram



(DPDT) 8501CO16 8501CDO16 8501CO22 8501CDO22