



Plug in relay, Type KU, blade, 0.5 HP at 240 VAC, 10A resistive at 120 VAC, 8 blade, DPDT, 2 NO, 2 NC, 24 VDC coil

8501KUDR12P14V53

Product availability: Stock - Normally stocked in distribution facility

Main

product range	8501K
product type	Relay
Relay Type	General purpose
mounting type	Socket
contact composition	DPDT
[Uc] control circuit voltage	24 V DC
pilot light	Indicator light relay energised LED

Complementary

horsepower rating	1 hp 277 V AC
	0.33 hp 120 V AC
breaking capacity	3 A 120 V AC inductive control circuit UL 508
	1.5 A 240 V AC inductive control circuit UL 508
	10 A 277 V AC resistive control circuit UL 508
	10 A 30 V DC resistive control circuit UL 508
maximum switching voltage	300 V AC
	30 V DC
contact material	Silver alloy (AgNi)
operating time	20 ms - pick-up
	20 ms - drop-out
shape of pins	Spade
for use with	8501NR82

Environment

ambient temperature range - operational	-4055 °C (-40131 °F)
product certifications	UL Listed UL Recognized CSA CE
Height	2.25 in (57.15 mm)
Width	1.37 in (34.80 mm)
Depth	1.4 in (35.6 mm)

Ordering and shipping details

Category	US10CP221144
Category	US10CP221

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discount Schedule	0CP2
GTIN	785901191063
Returnability	Yes
Country of origin	CN

Packing Units

PCE
1
1.70 in (4.318 cm)
1.70 in (4.318 cm)
3.00 in (7.62 cm)
3.040 oz (86.183 g)
PAL
108
40.00 in (101.6 cm)
36.00 in (91.44 cm)
48.00 in (121.92 cm)
22.701 lb(US) (10.297 kg)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	23	

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No