



NEMA Control Relay, Type X, utility, 10A resistive at 600 VAC, 12 normally open contacts, 125 VDC coil

8501XUDO1200V63

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	8501X	
Relay Type	Utility	
Product	Relay	
Current Rating	10 A AC 5 A DC	
Contact Configuration	12 NO 12 standard contact cartridges	
Number of Poles	12P	
Coil Voltage	125 V DC	
Voltage Rating	250 V DC	
Mounting Type	Panel	
Operating Temperature	-4071 °C (-40160 °F)	
Electrical Connection	Screw clamp terminals	
Certifications	CE UL Listed CSA	
Operating Time	37 ms - pick-up 21 ms - drop-out	
Height	3.56 in (90.42 mm)	
Width	2.23 in (56.64 mm)	
Depth	7.57 in (192.28 mm)	

Ordering and shipping details

Category	US10CP221157
Discount Schedule	0CP2
GTIN	785901743347
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	22.86 in (58.064 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Width	9.00 in (22.86 cm)	
Package 1 Length	58.06 in (147.484 cm)	
Package weight(Lbs)	4.050 lb(US) (1.837 kg)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	252	
Package 2 Height	40.00 in (101.6 cm)	
Package 2 Width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	
Package 2 Weight	1021.918 lb(US) (463.534 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	270	
Environmental Disclosure	Product Environmental Profile	

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No