MICRO SWITCH
FREEPORT ILLINOIS U S A
A DIVISION OF HONEYWELL

FED. MFG. CODE 91929

SWITCH-ENCLOSED

CATALOG LISTING
EXD-AR-3



MOUNTING BRACKET (1) AND 10-32 UNF X .250 REF PAN HEAD SCREW (2) FURNISHED UNASSEMBLED

SCALE - HALF SIZE



NO. 14 LEADS PVC INSULATION 36.000 MIN BEYOND HOUSING
3 (7)







THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

SCALE FULL

DO NOT SCALE PRINT

TOLERANCES
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

	DIM. mm	TOL. mm/m	DIM. in	TOL. mm/m
NO PLACES	X	1/.04		
ONE PLACE	X.X	0.4/.016	X.X	0.5/.00
TWO PLACES	X.XX	0.15/.006	X.XX	0.38/.015
THREE PLACES			X.XXX	0.13/.005
ANGLES				

DESIGN UNITS ☐ METRIC ■ US CUSTOMARY

RAW MATERIAL—COMMERCIAL STANDARD
MICRO SWITCH STANDARDS APPLY

DIMENSIONS ARE TO BE MET BEFORE PROTECTIVE COATINGS ARE APPLIED

WEIGHT

CHARACTERISTICS	ELECTRICAL DATA
OPERATING FORCE ——— 8-24 OZ	CONTACT ARRANGEMENT D P D T
RELEASE FORCE ——— 4-12 OZ	
PRETRAVEL ——— .250 MAX	
DIFFERENTIAL TRAVEL ——— .109 MAX	10A-125 OR 250 VAC 0.3A-125 VDC; 0.15A-250 VDC CODE L59
OVERTRAVEL ——— DO NOT OVERTRAVEL MORE THAN 25°	
BASIC SWITCH REPLACEMENT ——— DT-2R4-A7	

NOTES

1 - (8) MOUNTING SCREW HOLES, 10-32 UNF-2B THREADS X .219 REF. DEEP

2 - EXPLOSION PROOF-UNDERWRITERS LAB. INC. LISTED FOR HAZARDOUS LOCATIONS CLASS I, GROUPS B, C AND D, CLASS II, GROUPS E, F AND G.

3 COM LEADS - BLACK, N.C. LEADS - RED, N.O. LEADS - BLUE, GROUND LEAD - GREEN

EXD-AR-3 | M | RELEASE NO. PR-8880 | REPLACES

DRAWING NUMBER 6

ISSUE B

REVISIONS

A	CO 58360 CSH 9 NOV 85		
B	C060496 JAS 1 NOV 86		
C	C061381 DAW 23 APR 87		
D	C063239 TLB 22 MAR 88	CHECK	7 JUNE 88
E	C073019 MAM 19 SEP 92	CHECK	

DRAWN S L B 5 JUNE 80 CHECK

FD-52851-A

41