

Data sheet

RP025xxIBLC (Type 137)

Page 1/6

P/N

311371xx

xx=number of poles


2026/08/17

Version: AC

Illustrations



Dimensional drawing as an example



See enlarged drawings at the end of document

Product specification

- screw type terminal block, pluggable
- centerline 5.00 mm, direction of connection 90°
- lift system, fittable without loss of poles
- color black
- wire entry perpendicular to plug direction, lamella



Data sheet

RP025xxIBLC (Type 137)

Page 2/6

P/N
311371xx

xx=number of poles

2026/08/17

Version: AC

Technical Data

General Data

Tightening torque SEV	0.5 Nm		
Tightening torque UL	4.4 lb-in		
Insulating material class	CTI 600		
clearance/creepage dist.	3.2 mm		
Protection category	IP20		
Insul. strip length	8 mm		
Rated current	10 A		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Rated voltage	250 V	630 V	630 V
Rated test voltage	4 kV	4 kV	4 kV

Terminal data

rat.wiring solid AWGmax	0.13 mm ² - 2.5 mm ² / AWG 26 - AWG 12
rat.wiring strand.AWGmax	0.13 mm ² - 2.5 mm ² / AWG 26 - AWG 12

Approvals

 V / A / AWG	300 / 15 / 26 - 12
approval UL - File No.	E121004
	250 V / 2.5 kV / 10 A

Material

insulating material	PA66
flammability class	V0
contact material	CuBe
Contact surface	Ni + Ag
terminal body thread	M3
terminal body material	CuZnPb
terminal body surface	Cu + Ni
screw thread	M3
screw material	8,8
screw surface	Zn Cr(VI)-frei/free
wire protector material	CuNiZn

Data sheet
RP025xxIBLC (Type 137)

Page 3/6

P/N
311371xx**xx=number of poles**

2026/08/17

Version: AC

Technical Data

Glow-Wire Flammability GWFI	960 °C acc. to IEC 60695-2-12
Glow-Wire Flammability GWIT	775 °C acc. to IEC 60695-2-13

Climatic Data

upper limit temperature	105 °C
lower limit temperature	-40 °C

general

Tolerance	ISO 2768 -mH
-----------	--------------

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).



Data sheet

Page 4/6

RP025xxIBLC (Type 137)

P/N

311371xx

xx=number of poles

2026/08/17

Version: AC

Accessories

P/N	Designation
716846	Coding comb pastel blue
720161-01-2	720161
720161-02-2	720161
750313	Mounting flange right for type 137
750314	Mounting flange left for type 137



Data sheet

Page 5/6

RP025xxIBLC (Type 137)

P/N

311371xx

xx=number of poles

2026/08/17

Version: AC

Counterpart

P/N	Designation
310271	PR015xxVBVC (Type 027)



Data sheet

RP025xxIBLC (Type 137)

Page 6/6

P/N

311371xx


xx=number of poles

2026/08/17

Version: AC

Illustrations

Dimensional drawing as an example



$L = (\text{pole size} - 1) \times \text{centerline} + 5 \text{ mm } [0.197]$

