STL 950/3/5,08-H-G OG

11677.3



Male pin block, No. of poles: 3, Width: 15.24 mm, Colour: Orange

Commercial

General

Colour: Orange
Connector version: Attached plug-in connector
Country of origin: TN
Customs number: 85366930
GTIN (EAN): 4044211103354
Packaging type: Carton
Packaging unit: 50
Quantity unit: PC
Type of banding: Without
Unit of weight: G
Weight per piece (including packaging): 1.56g
Weight per piece (not including packaging): 1.1g

Technical

Dimensions

Diameter of connecting pin: 1mm
Drill hole diameter: 1.4mm
Height: 8.4mm
Length: 12mm
Length of the pin: 3.5mm
Pitch: 5.08mm

Width: 11.36mm

Width left: 3.14mm

Width right: 3.14mm

Ratings

Contamination degree: 3

Overvoltage category: III

Rated current: 12A

Rated impulse voltage: 4kV

Rated voltage: 250V

Connection data

Angle of PCB/contact: 0°/180° (horizontal)

No. of poles: 3

Number of plug-in rows: 1

Further technical data

Creepage-current resistance: CTI 600

GWFI after-glow time: 30Sek.

GWIT exposure time: 5Sek.

Glow wire flammability index GWFI: GWFI 850

Glow wire ignition temperature GWIT: GWIT 775°C

Insulation resistance: 1*10^13Ohm x cm

Plug-in cycles acc. to standard: 100

Recommended wave soldering duration, max.: 4Sek.

Recommended wave soldering duration, min.: 3Sek.

Recommended wave soldering temperature: 265°C

Storage temperature, max.: 105°C

Storage temperature, min.: -40°C

Materials

Contact pin: Copper alloy

Flammability class UL 94: V-0

Insulation housing: Polyamide 6.6

Working temperature, max.: 105°C

Working temperature, min.: -30°C

Approvals

cUL Recognized

cUL Recognized: 1
cUL Usegroup B: rated current: 15A
cUL Usegroup B: rated voltage: 300V
cUL Usegroup C: rated current: 15A
cUL Usegroup C: rated voltage: 150V
cUL Usegroup D: rated current: 10A
cUL Usegroup D: rated voltage: 300V
cUL approval: CSA 22.2 No.158
cUL wire material: Cu

UL Recognized

UL Recognized: 1
UL Usegroup B: rated current: 15A
UL Usegroup B: rated voltage: 300V
UL Usegroup C: rated current: 15A
UL Usegroup C: rated voltage: 150V
UL Usegroup D: rated current: 10A
UL Usegroup D: rated voltage: 300V
UL approval: UL 1059
UL factory wiring: ✓
UL wire material: Cu

VDE approval

VDE approval: DIN EN 61984
VDE approval granted: ✓
VDE contamination degree: 3
VDE overvoltage category: III
VDE rated current: 12A
VDE rated impulse voltage: 4kV
VDE rated voltage: 250V

Environment

Environmental Product Compliance

EU-POP Conform: Yes

PROP 65 Conform: Yes

REACH Candidate Substance Note: No

REACH Conform: Yes

REACH Reference date: 2026-02-04

RoHS Conform: Yes

TSCA Conform: Yes