


SL 16/35/N GNYE

1533.2



M5



EAC

Protective earth terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 16 mm², Width: 12 mm, Colour: Green-yellow

Commercial

General

Colour: Green-yellow

Country of origin: CZ

Customs number: 85369010

GTIN (EAN): 4044211047153

Packaging unit: 50

Product description: Protective earth terminal

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 54.4g

Weight per piece (not including packaging): 52.8g

Technical

Dimensions

Height TS 35/7.5: 53mm

Length: 50mm

Width: 12mm

Ratings

Contamination degree: 3

Overvoltage category: III

Rated cross-section: 16mm²

Connection data

Connection position: Lateral

Connection principle: Screw connection

Connections: 2

Number of levels: 1

Number of terminals per level: 2

Screw head: Slotted

Screw threading: M 5

Stripping length: 15mm

Tightening torque, max.: 4Nm

Tightening torque, min.: 2Nm

Wire cross-section AWG, max.: 4

Wire cross-section AWG, min.: 10

Wire cross-section single core (rigid)/stranded, max.: 25mm²

Wire cross-section single-core (rigid) / stranded, min.: 2.5mm²

Wire cross-section stranded with wire-end ferrules, max.: 16mm²

Wire cross-section stranded with wire-end ferrules, min.: 2.5mm²

Wire cross-section stranded, max.: 16mm²

Wire cross-section stranded, min.: 2.5mm²

Further technical data

Gauge plug acc. to EN 60 947-1: B7

Mounting type: Mounting rail TS 35/7,5

Number of cross-connection channels: 1

Tightening torque, fastening screw max.: 2.4Nm

Tightening torque, fastening screw min.: 1.2Nm

Materials

Flammability class UL 94: V-2

Insulation housing: Polyamide 6.6

Working temperature, max.: 105°C

Working temperature, min.: -40°C

Approvals

Standards and regulations

EAC approval: TR ZU 004/2013

EAC approval granted: ✓

KEMA KEUR approval

KEMA KEUR approval: EN 60947-7-2:2009

KEMA KEUR approval granted: ✓

KEMA wire cross-section single core (rigid), min.: 1.5mm²

KEMA wire cross-section single-core (rigid), max.: 25mm²

KEMA wire cross-section stranded, max.: 16mm²

KEMA wire cross-section stranded, min.: 1.5mm²

CSA approval

: 042110_0_000

CSA approval: C22.2 No 158

CSA approval granted: ✓

CSA stripping length: 15mm

CSA wire cross-section AWG, max.: 6

CSA wire cross-section AWG, min.: 12

CSAus approval

: 042110_0_000

CSAus approval: UL 1059

CSAus approval granted: ✓

CSAus stripping length: 15mm

CSAus wire cross-section AWG, max.: 6

CSAus wire cross-section AWG, min.: 12

Environment

Environmental Product Compliance

EU-POP Conform: Yes

PROP 65 Conform: Yes

REACH Candidate Substance Note: No

REACH Conform: Yes


REACH Reference date: 2025-06-25

RoHS Conform: Yes

TSCA Conform: Yes

Accessories

Quick marking



PMC SB 6/50 WH

4702.7

Screwdriver



SDB 0,8x4,0

1087.0
