


SRK 4/2A SAS OG

17116.3



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6 mm, Colour: Orange

Commercial

General

Colour: Orange

Country of origin: DE

Customs number: 85369010

GTIN (EAN): 4044211170219

Packaging unit: 80

Product description: Feed-through terminal

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 11.1g

Weight per piece (not including packaging): 10.2g

Technical

Dimensions

Height TS 35/7.5: 47mm

Length: 62.5mm

Width: 6mm

Ratings

Contamination degree: 3

Current load, max.: 41A

Maximum power dissipation for nominal condition: 1.02W

Overvoltage category: III

Rated cross-section: 4mm²

Rated current: 32A

Rated impulse voltage: 8kV

Rated voltage: 400V

Connection data

Connection position: Lateral

Connection principle: Screw connection

Connections: 4

Number of levels: 1

Number of terminals per level: 2

Screw head: Slotted

Screw threading: M 3

Special connection: Spade flat plug Faston 2.8mm

Stripping length: 10mm

Tightening torque, max.: 1Nm

Tightening torque, min.: 0.5Nm

Wire cross-section AWG, max.: 10

Wire cross-section AWG, min.: 26

Wire cross-section single core (rigid)/stranded, max.: 6mm²

Wire cross-section single-core (rigid) / stranded, AWG max.: 10

Wire cross-section single-core (rigid) / stranded, AWG min.: 26

Wire cross-section single-core (rigid) / stranded, min.: 0.2mm²

Wire cross-section stranded with wire-end ferrules, AWG max.: 12

Wire cross-section stranded with wire-end ferrules, AWG min.: 26

Wire cross-section stranded with wire-end ferrules, max.: 4mm²

Wire cross-section stranded with wire-end ferrules, min.: 0.2mm²

Wire cross-section stranded, AWG max.: 10

Wire cross-section stranded, AWG min.: 26

Wire cross-section stranded, max.: 6mm²

Wire cross-section stranded, min.: 0.2mm²

Further technical data

End plate required: ✓

Gauge plug acc. to EN 60 947-1: A4

Mounting type: Mounting rail TS 35/7,5

Number of cross-connection channels: 2

Number of test pick-off options: 1

Materials

Flammability class UL 94: V-0

Insulation housing: Polyamide 6.6

Working temperature, max.: 120°C

Working temperature, min.: -40°C

Approvals

Standards and regulations

EAC approval: TR ZU 004/2011

EAC approval granted: ✓

Environment

Environmental Product Compliance

EU-POP Conform: Yes

PROP 65 Conform: Yes

REACH Candidate Substance Note: No

REACH Conform: Yes

REACH Reference date: 2025-06-25

RoHS Conform: Yes

TSCA Conform: Yes

Accessories

Screwdriver



SDB 0,6x3,5

1086.0

Cover



SAD 1/6/B YE

17296.8

Measurement pick-off terminal



SMAG 4/2,5 BG
[17120.2](#)

End plate



AP 2,5-10 RB
[2001.0](#)

End stop

SES 35 GN
[17250.1](#)


Insulation cap for cross-connector

SQIK 2,5-10 BK
[17200.4](#)

Insulated cross-connector

SQI 4/3 BK
[17212.4](#)

Quick marking




PMC SB 6/50 WH
[4702.7](#)

Test adapters



STA 5/1 BG
[17260.2](#)



STA ZP1 BG

17261.2



STA 5/1 BG

17260.2



STA ZP1 BG

17261.2
