



# SRK 2,5/2A SAS OG

## 17119.3



**M2.5** 



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm<sup>2</sup>, Width: 5 mm, Colour: Orange

## Commercial

### General

Colour: Orange

Country of origin: DE

Customs number: 85369010

GTIN (EAN): 4044211170073

Packaging unit: 80

Product description: Feed-through terminal

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 9.06g

Weight per piece (not including packaging): 8.3g

## Technical

### Dimensions

Height TS 35/7.5: 47mm

Length: 62.5mm

Width: 5mm

### Ratings

Contamination degree: 3

Current load, max.: 32A

Maximum power dissipation for nominal condition: 0.77W

Overvoltage category: III

Rated cross-section: 2.5mm<sup>2</sup>

Rated current: 24A

Rated impulse voltage: 8kV

Rated voltage: 400V

### Connection data

Connection position: Lateral

Connection principle: Screw connection

Connections: 4

Number of levels: 1

Number of terminals per level: 2

Screw head: Slotted

Screw threading: M 2,5

Special connection: Spade flat plug Faston 2.8mm

Stripping length: 10mm

Tightening torque, max.: 0.8Nm

Tightening torque, min.: 0.4Nm

Wire cross-section AWG, max.: 12

Wire cross-section AWG, min.: 30

Wire cross-section single core (rigid)/stranded, max.: 4mm<sup>2</sup>

Wire cross-section single-core (rigid) / stranded, AWG max.: 12

Wire cross-section single-core (rigid) / stranded, AWG min.: 30

Wire cross-section single-core (rigid) / stranded, min.: 0.2mm<sup>2</sup>

Wire cross-section stranded with wire-end ferrules, AWG max.: 14

Wire cross-section stranded with wire-end ferrules, AWG min.: 30

Wire cross-section stranded with wire-end ferrules, max.: 2.5mm<sup>2</sup>

Wire cross-section stranded with wire-end ferrules, min.: 0.2mm<sup>2</sup>

Wire cross-section stranded, AWG max.: 12

Wire cross-section stranded, AWG min.: 30

Wire cross-section stranded, max.: 4mm<sup>2</sup>

Wire cross-section stranded, min.: 0.2mm<sup>2</sup>

### Further technical data

End plate required: ✓

Gauge plug acc. to EN 60 947-1: A3

Mounting type: Mounting rail TS 35/7,5

Number of cross-connection channels: 2

---

Number of test pick-off options: 1

## Materials

---

Flammability class UL 94: V-0

Insulation housing: Polyamide 6.6

Working temperature, max.: 120°C

Working temperature, min.: -40°C

---

## Approvals

---

### Standards and regulations

---

EAC approval: TR ZU 004/2011

EAC approval granted: ✓

---

## Environment

---

### Environmental Product Compliance

---

EU-POP Conform: Yes

PROP 65 Conform: Yes

REACH Candidate Substance Note: No

REACH Conform: Yes

REACH Reference date: 2025-06-25

RoHS Conform: Yes

TSCA Conform: Yes

---

## Accessories

---

### Screwdriver

---



**SDB 0,5x3,0**  
1085.0

### Cover

---



**SAD 1/5/B YE**  
17295.8

---

## End plate

---



**AP 2,5-10 RB**  
[2001.0](#)

---

## End stop

---

**SES 35 GN**  
[17250.1](#)

---

## Insulation cap for cross-connector

---

**SQIK 2,5-10 BK**  
[17200.4](#)

---

## Insulated cross-connector

---



**SQI 2,5/4 BK**  
[17203.4](#)

---

**SQI 2,5/6 BK**  
[17205.4](#)

---

**SQI 2,5/9 BK**  
[17208.4](#)

---



**SQI 2,5/30 BK**  
[17210.4](#)

---



**SQI 2,5/3 BK**  
[17202.4](#)

---

**SQI 2,5/5 BK**  
[17204.4](#)

---



**SQI 2,5/2 BK**  
[17201.4](#)

---

**SQI 2,5/7 BK**

17206.4

---

**SQI 2,5/8 BK**

17207.4

---




**SQI 2,5/10 BK**

17209.4

---

## Quick marking

---



**PMC SB 5/50 WH**

4600.7

---

## Partition plate

---



**TW 2,5-10 RB**

2002.0

---

## Test adapters

---



**STA 5/1 BG**

17260.2

---



**STA 5/1 BG**

17260.2

---