



SRK 2,5/2A SAS BK

17119.4



M2.5 



Feed-through terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Black

Commercial

General

Colour: Black

Country of origin: DE

Customs number: 85369010

GTIN (EAN): 4044211170042

Packaging unit: 80

Product description: Feed-through terminal

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 9.06g

Weight per piece (not including packaging): 8.3g

Technical

Dimensions

Height TS 35/7.5: 47mm

Length: 62.5mm

Width: 5mm

Ratings

Contamination degree: 3

Current load, max.: 32A

Maximum power dissipation for nominal condition: 0.77W

Overvoltage category: III

Rated cross-section: 2.5mm²

Rated current: 24A

Rated impulse voltage: 8kV

Rated voltage: 400V

Connection data

Connection position: Lateral

Connection principle: Screw connection

Connections: 4

Number of levels: 1

Number of terminals per level: 2

Screw head: Slotted

Screw threading: M 2,5

Special connection: Spade flat plug Faston 2.8mm

Stripping length: 10mm

Tightening torque, max.: 0.8Nm

Tightening torque, min.: 0.4Nm

Wire cross-section AWG, max.: 12

Wire cross-section AWG, min.: 30

Wire cross-section single core (rigid)/stranded, max.: 4mm²

Wire cross-section single-core (rigid) / stranded, AWG max.: 12

Wire cross-section single-core (rigid) / stranded, AWG min.: 30

Wire cross-section single-core (rigid) / stranded, min.: 0.2mm²

Wire cross-section stranded with wire-end ferrules, AWG max.: 14

Wire cross-section stranded with wire-end ferrules, AWG min.: 30

Wire cross-section stranded with wire-end ferrules, max.: 2.5mm²

Wire cross-section stranded with wire-end ferrules, min.: 0.2mm²

Wire cross-section stranded, AWG max.: 12

Wire cross-section stranded, AWG min.: 30

Wire cross-section stranded, max.: 4mm²

Wire cross-section stranded, min.: 0.2mm²

Further technical data

End plate required: ✓

Gauge plug acc. to EN 60 947-1: A3

Mounting type: Mounting rail TS 35/7,5

Number of cross-connection channels: 2

Number of test pick-off options: 1

Materials

Flammability class UL 94: V-0

Insulation housing: Polyamide 6.6

Working temperature, max.: 120°C

Working temperature, min.: -40°C

Approvals

Standards and regulations

EAC approval: TR ZU 004/2011

EAC approval granted: ✓

Environment

Environmental Product Compliance

EU-POP Conform: Yes

PROP 65 Conform: Yes

REACH Candidate Substance Note: No

REACH Conform: Yes

REACH Reference date: 2025-06-25

RoHS Conform: Yes

TSCA Conform: Yes

Accessories

Screwdriver



SDB 0,5x3,0
1085.0

Cover



SAD 1/5/B YE
17295.8

End plate



AP 2,5-10 RB

2001.0

End stop

SES 35 GN

17250.1

Insulation cap for cross-connector

SQIK 2,5-10 BK

17200.4

Insulated cross-connector



SQI 2,5/4 BK

17203.4

SQI 2,5/6 BK

17205.4

SQI 2,5/9 BK

17208.4



SQI 2,5/30 BK

17210.4



SQI 2,5/3 BK

17202.4

SQI 2,5/5 BK

17204.4



SQI 2,5/2 BK

17201.4

SQI 2,5/7 BK

17206.4

SQI 2,5/8 BK


17207.4



SQI 2,5/10 BK

17209.4

Quick marking



PMC SB 5/50 WH

4600.7

Partition plate



TW 2,5-10 RB

2002.0

Test adapters



STA 5/1 BG

17260.2



STA 5/1 BG

17260.2
