Datasheet

3717.8
ZQI 2,5/9 YE
ZQI 2,5/9 YE



Insulated cross-connector, No. of poles: 9, Mounting type: Plug in, Width: 44.8 mm, Rated cross-section: 2.5 mm², Colour: Yellow

Business data

Product description	Insulated cross-connector
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	5.2
Weight per piece (including packaging)	5.24
Unit of weight	G
Customs number	85389099
Country of origin	DE

© **CONTA-CLIP Verbindungstechnik GmbH** | Otto-Hahn-Str. 7 | D-33161 Hövelhof
Fon +49 (0) 52 57.98 33-0 | Fax +49 (0) 52 57.98 33-33 | E-Mail info@conta-clip.de | conta-clip.de

Creation date 24.02.2021 01:29:44
Subject to technical modifications

Datasheet

3717.8
ZQI 2,5/9 YE
ZQI 2,5/9 YE

Technical Data

Dimensions	
Length	4.5 mm
Width	44.8 mm
Pitch size	5 mm

Ratings	
Voltage with partition, max.	800 V
Voltage without partition, max.	800 V
Rated current	24 A
Rated cross-section	2.5 mm²
Contamination degree	3

Connection data	
No. of poles	9

Datasheet

3717.8
ZQI 2,5/9 YE
ZQI 2,5/9 YE

Technical Data

Materials

Material	Copper alloy
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	9