





APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/9/17	



RECOMMENDED PCB LAYOUT



SPECIFICATIONS:

Material:

Insulator: Hi-Temp Thermoplastic, rated UL 94V-0

Insulator color: Natural

Contacts: Phosphor Bronze

Plating:

Tin over Copper underplate overall

Electrical:

Voltage rating: 100 V AC/DC

Current rating: AC/DC 1 A

Contact resistance: 20 mohms max

Insulation resistance: 500 Mohms min

Dielectric withstanding voltage: 500 VAC for 1 minute

Temperature Rating:

Operating temperature: -25°C to +85°C

Environmental:

Lead free, RoHS compliant



PACKAGED ON TAPE & REEL

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MILLIMETERS
TOLERANCES: EXCEPT AS NOTED
HOLES
MM
.X ± .25
.XX ± .15
.XXX ± .05

Ø.XX ± .013

APPROVALS		DATE
DRAWN	HR	3/9/17
CHECKED	AC	3/9/17
APPROVED		

ADAM TECH

909 Rahway Avenue, Union, NJ 07083

Phone: 908-687-5000 Fax: 908-687-5710

TITLE
.049 [1.25] PITCH WIRE TO BOARD HEADER
RIGHT ANGLE, SMT TYPE, W/ MYLAR

SIZE	PART NO.	REV.
X	125SH-D-02-TR-SMT-KT-T/R	-
REF: S00015T	SCALE: NTS	SHEET 1 OF 2

6

5

4

3

2

1

APPROVED: _____

DATE: _____ TITLE: _____

Rev



AWO #

Description

Date

Appr

SEE SHT 1 OF 2 FOR REVISION



UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED
INCHES HOLES
.X ± .10 Ø.X ± .10
.XX ± .020 Ø.XX ± .015
.XXX ± .015 Ø.XXX ± .010

APPROVALS

DATE

DRAWN

HR

3/9/17

CHECKED

AC

3/9/17

APPROVED

ADAM TECH

909 Rahway Avenue, Union, NJ 07083

Phone: 908-687-5000 Fax: 908-687-5710

TITLE
.049 [1.25] PITCH WIRE TO BOARD HEADER
RIGHT ANGLE, SMT TYPE, W/ MYLAR

SIZE

X

PART NO.

125SH-D-02-TR-SMT-KT-T/R

REV.

-

REF: S00015T

SCALE: NTS

SHEET 2 OF 2

6

5

4

3

2

1