

Rev	AWO #	Description	Date	Appr
-		RELEASED	3/27/20	


APPROVED: _____


DATE: _____ TITLE: _____






RECOMMENDED PCB LAYOUT





SECTION A–A



ASSEMBLY VIEW

SPECIFICATIONS:

Material:
Insulator: Hi–temp thermoplastic, rated UL 94V–0
Insulator color: Natural
Contacts: Brass
Plating:
Gold flash over Nickel underplate overall
Electrical:
Voltage rating: 50 AC/DC
Current rating: 1 AC/DC
Contact resistance: 20 mohms max
Insulation resistance: 500 Mohms min
Dielectric withstanding voltage: 500 VAC for 1 minute
Temperature Rating:
–25°C to +85°C
Environmental:
Lead free, RoHS compliant.

RoHS COMPLIANT

PACKAGED ON TAPE & REEL

Positions: 02 thru 15
A= .059 [1.50] X No. of Spaces
B= .059 [1.50] X No. of Positions + .118 [3.00]
C= .059 [1.50] X No. of Positions + .024 [0.60]

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	AY	3/27/20
CHECKED	IW	3/27/20
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: .059 [1.50] TOP ENTRY TYPE, SMT TYPE

SIZE	PART NO.	REV.
X	15SH-A-XX-GS-SMT-T/R	-

REF: S00124T | SCALE: NTS | SHEET 1 OF 1