

Rev	AWO #	Description	Date	Appr
-		RELEASED	9/8/20	


APPROVED: _____


DATE: _____ TITLE: _____





RECOMMENDED PCB LAYOUT





PACKAGED ON TAPE & REEL

Positions: 02 thru 13

A=.059 [1.50] X No. of Spaces

B=.059 [1.50] X No. of Spaces + .177 [4.50]

SPECIFICATIONS:

Material:

Insulator: Hi–Temp Thermoplastic, rated UL 94V–0

Insulator color: Natural

Contacts: Brass, Tin plated

Electrical:

Voltage rating: 100V AC/DC

Current rating: 1A AC/DC

Contact resistance: 20 mohms max

Insulation resistance: 500 Mohms min

Dielectric withstanding voltage: 500 VAC for 1 minute

Environmental:

Lead free, RoHS compliant.

RoHS COMPLIANT

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

APPROVALS		DATE
DRAWN	AY	9/8/20
CHECKED	NP	9/8/20
APPROVED		

ADAM TECH INTERCONNECTS
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: .059 [1.50] WAFER ,RIGHT ANGLE SMT TYPE, TIN PLATED

SIZE	PART NO.	REV.
X	15SH-A3-XX-TR-SMT-T/R	-

REF: S00015T | SCALE: NTS | SHEET 1 OF 1