





Rev	AWO #	Description	Date	Appr
-		RELEASED	5/9/13	

APPROVED: _____

DATE: _____ TITLE: _____



Recommended PCB Layout



SPECIFICATIONS:

Material:

Insulator: Hi-temp thermoplastic, rated UL 94V-0

Insulator color: Beige

Contacts: Brass

Plating:

Tin over copper underplate overall.

Electrical:

Operating voltage: 250 VAC max

Current rating: 3 Amps max

Contact resistance: 20 mohms max

Dielectric withstanding voltage: 1000 VAC for 1 minute

Mechanical:

Temperature Rating:

Operating temperature: -40°C to +105°C

Environmental:

Lead free, RoHS compliant

Positions: 02 thru 20

A = .098 [2.50] x No. of Spaces

B = .098 [2.50] x No. of Spaces + .197 [5.00]

ADAM TECH

909 Railway Avenue, Union, NJ 07083

Phone: 908-687-5000 Fax: 908-687-5710

.098 [2.50] PITCH WAFER, STRAIGHT PCB

LOW PROFILE

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED INCHES Holes .X ± .10 ØX ± .10 .XX ± .020 ØXX ± .015 .XXX ± .015 ØXXX ± .010				APPROVALS				DATE			
DRAWN	AY			5/9/13							
CHECKED	AH			5/9/13							
APPROVED											

6

5

4

3

2

1